



Autoclaves for sterilization “Presoclave PLUS” 50, 80 and 150 litres.



MICROPROCESSOR TEMPERATURE AND CYCLE CONTROL AND ATMOSPHERIC PURGE.
ELECTRONIC CONTROL OF TIME AND TEMPERATURE RANGE FROM 115 °C TO 134 °C. (0.62 TO 2 bar).
CONFORMS TO APPARATUS PRESSURE REGULATION DIRECTIVES.
PROCESS REGISTRATION AND DOWNLOAD VIA USB. VERTICAL MODEL: 50, 80 AND 150 LITRES.

SAFETY:

SAFETY OVER PRESSURE VALVE: PREVENTS OVER PRESSURE ABOVE THE MAXIMUM SET LIMIT.
SAFETY PRESSURE SWITCH: DISCONNECTS POWER TO THE HEATER IF THE UNIT EXCEEDS THE MAXIMUM PRESSURE LIMIT.
SAFETY THERMOSTAT AND WATER LEVEL: DISCONNECT POWER TO THE HEATER IF INSUFFICIENT WATER OR OVER TEMPERATURE.
SAFETY LID: PREVENTS THE LID BEING OPENED IF THE CHAMBER IS UNDER PRESSURE.
SAFETY INSULATION: THERMALLY INSULATED LID .

An economic semi-automatic alternative

FEATURES

External case made from stainless steel.
INCOLOY stainless steel heater elements, hard waring, resistant to corrosion and high temperatures.

Process registration and download via usb.

External lateral probe port (only models 50 and 80 litres).
Sterilization chamber and door made from stainless steel.
Automatic purge to atmosphere.
10 programs configurable by the user.

CONTROL PANEL

1. TFT touch screen with virtual push buttons.
2. Pressure gauge.
3. Push button open lid.



MODELS	Part No.	Capacity litres	Ø Height (usables cm)	Height / Width / Depth (exterior cm)	Power W	Weight Kg
PRESOCLAVE III 50	4001770	50	30 70	117 48 62	3600	75
PRESOCLAVE III 80	4001771	80	40 62	119 58 72	3600	100
PRESOCLAVE II 150	*4001772	150	50 70	118 80 95	7500	225

Does not include baskets and drums, order separately. Part No. 4001772 due to its consumption is manufactured for three-phase current at 230 V or 400 V to be specified.



ACCESSORIES: AISI 304 Stainless steel wire baskets and drums.

For Presoclave III 50 Plus, Part. no: 4001770.
Capacity, 3 baskets Ø 25 and 20 cm. height. Part No. **1000495**
For Presoclave III 80 Plus, Part. no: 4001771.
Capacity, 2 baskets Ø 36 and 28 cm. height. Part No. **1000496**
For Presoclave II 150 Plus, Part. no: 4001772.
Capacity, 2 baskets Ø 44 and 22 cm height. Part No. **1000780**
Sterilization drum made from AISI 304 stainless steel.
For Presoclave III 50 Plus, Part. no: 4001770.
Capacity, 3 drum Ø 25 and 18 cm. height. Part No. **1002418**
For Presoclave III 80 Plus, Part. no: 4001771.
Capacity, 2 drum Ø 35 and 27 cm. height. Part No. **1002419**
Detergent Bio-Sel.
Water distillation unit especially for autoclaves.
Purge microfilter. Part No. **4001221**
Loading and unloading crane. Part No. **1002426** (see page 61).



BACK VIEW:

1. Safety valve.
2. Mains power.
3. Safety thermostat
4. Steam empty valve and Drain selector valve.
5. USB connector.

COMPLEMENTS That needs to be factory installed:
Pt100 second sensor only temperature reader. Part No. **4001219** (see page 63).
Printer of continuous paper roll with print out of program, temperature, pressure, time and phase. Part No. **4002417**