


**GENERAL
CATALOGUE**

Instruments for Water Analysis
Volume 18

 milwaukee



COMMITTED TO TOTAL CUSTOMER SATISFACTION

Milwaukee is a dynamic worldwide manufacturer of electrochemical Instrumentation for water analysis to measure pH, Redox, Conductivity, Salinity, Dissolved Oxygen, Temperature, Turbidity, Chlorine, Ammonia, Chloride, Phosphate, Iron, etc.

Milwaukee serves all markets where water quality measurements are required: Laboratory market, food and beverage, environmental, education and government, water and waste water treatment, pharmaceutical and biotechnology, chemical, agriculture and horticulture, hydroponics, aquariums, swimming pools, etc.

Thanks to your valuable feedback our R&D team has designed a new line of instruments for laboratory and field measurements.



Many of our instruments combine 2 or more parameters providing added versatility and excellent value for money. With an extended range of products, from basic hand held instruments to high performance laboratory bench meters, Milwaukee products have a reputation for reliability and accuracy.

All of our instruments are supplied with probes, electrode holders, buffer solutions and many come in a hard carrying case and ready for use.

Milwaukee Instruments are available worldwide through a selected network of distributors and associated companies that are committed to Total Customer Satisfaction.

Everyone in Milwaukee Instruments is committed to exceeding your expectations.

Global Offices



Milwaukee Electronics Kft.
Europe, South America, Africa,
Asia, Middle East and Pacific Rim

Milwaukee Electronics Kft.

Alsó-Kikötő sor 11.C
H-6726 Szeged - HUNGARY
tel: +36 62 428 050
fax: +36 62 428 051
e-mail: sales@milwaukeeinst.com


























Milwaukee Instruments, Inc.
United States of America

Milwaukee Instruments, Inc.

2950 Business Park Drive
Rocky Mount - NC 27804 - U.S.A.
tel: +1 252 443 3630
fax: +1 252 443 1937
e-mail: sales@milwaukeetesters.com

Beauty of

Symbols

-  **CE**
CE Certified products
-  **IP65**
IP65 rated housing
-  **IP67**
IP67 rated housing
-  **GLP (Good Laboratory Practices)**
Good Laboratory Practices requires that time and date should be recorded with the parameters measured
-  **USB Port**
Communication via opto-isolated USB port
-  **2 Years Warranty**
Instruments are covered by 2 years warranty
-  **3 Years Warranty**
Instruments are covered by 3 years warranty
-  **7 pH Memorized buffers**
7 pH Memorized buffers for calibration
-  **MEM**
MEM key allows to memorize the last measurement
-  **LOG**
LOG key allows to save up to 1000 measurements
-  **ALARM**
A LED light warns the user in the event the reading is outside the set point
-  **2 Point Calibration**
Calibration can be performed at 1 or 2 points
-  **3 Point Calibration**
Calibration can be performed at 1, 2 or 3 points
-  **5 Point Calibration**
Calibration can be performed at 3 or 5 points
-  **Multiparameter instruments**
Instruments that measure more than 1 parameter
-  **Automatic Temperature Compensation**
Automatically corrects the measured value based on the temperature of the solution
-  **Manual Temperature Compensation**
Is a method for temperature compensation through the manual input of sample temperature value
-  **Auto-Buffer**
Auto-Buffer Recognition ensures that correct buffer values are used during calibration
-  **Dual Level Display**
Displays simultaneously 2 parameters
-  **Replaceable Electrode**
Instrument with replaceable electrode
-  **Self-diagnostics Messages**
Messages on the LCD to make the calibration easy and accurate
-  **LED**
The lightsource is the LED with different wavelengths
-  **Backlight**
Backlit LCD

Contents

Highlights	2
New Meters	3
New Bench Meters	4
pH/ORP/Temp Measurements	
pH/ORP/Temp Bench Meters	6
pH Electrodes	
pH Electrodes basic	9
pH/ORP/Temp Measurements	
pH/ORP/Temp Portable Meters (Professional)	14
Budget pH/ORP/Temp Portable Meters	16
pH Measurements in Soil	17
pH Measurements in Cheese	18
pH/Temp Pocket Testers (Professional)	19
pH/ORP/Temp Pocket Testers (Professional)	20
pH Testers	21
pH Monitors	22
pH/ORP Controllers	23
Peristaltic Dosing Pumps	24
Conductivity/TDS/NaCl/Temp Measurements	
EC/TDS/NaCl/Temp Bench Meter	25
EC/TDS/NaCl/Temp Portable Meter (Professional)	26
Budget EC/TDS Portable Meters	27
EC/TDS/Temp Pocket Testers (Professional)	28
EC/TDS Testers	29
EC/TDS Monitors	30
New EC Meters (MC311, EC40)	31
Dissolved Oxygen/Temp Measurements	
DO/Temp Bench Meter	32
DO/Temp Portable Meter (Professional)	33
Budget DO/Temp Portable Meter	34
Multiparameter Measurements	
Budget pH/EC/TDS Portable Meters	35
pH/ORP/EC/TDS/NaCl/Temp Bench Meters	36
pH/EC/TDS/Temp Portable Meters (Professional)	37
pH/EC/TDS/Temp Pocket Testers (Professional)	38
pH/EC/TDS/Temp Monitors	39
Light Measurements	
LUX Portable Meter	40
Colorimetric Measurements	
Free, Total Chlorine & pH Portable Photometer	41
Ammonia, Iron & Phosphate Portable Photometers	42
Free, Total Chlorine & Chloride Portable Photometers	43
Handy Photometers: Free & Total Chlorine	44
Handy Photometers: Phosphate, Iodine, Iron	45
Peroxide Value Photometer	46
Turbidity Measurements	
Turbidity Portable Meter	47
Refractometers	
Digital Refractometers for Brix, Fructose, Glucose and Invert Sugar	48
Digital Refractometers for Wine and Grape Product Measurements	49
Digital Refractometer for Sodium Chloride Measurements	50
Salt in Cheese Measurements	51
Digital Refractometer for Seawater Measurements	52
Digital Refractometer for Ethylene Glycol Measurements	53
Thermometers & NPK Test Kit	54
Mini-Titrators	55
pH Measurement in Meat	56
Electrodes & Probes	57
Electrode selection guide	58
Calibration, Maintenance & Cleaning Solutions	59
Warranty	60

simplicity

Highlights in this Catalogue



The innovative line of Milwaukee MAX bench meters includes a lot of new features:

- pH extended range: -2.00 to 20.00 pH, -2.000 to 20.000 pH
- Rechargeable battery with 8 hrs battery life
- 2 USB ports: Standard USB socket to export data directly to a flash drive and micro USB to connect a computer for file export
- Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time
- Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots)
- Electrode diagnostics feature checks and displays the condition of the pH electrode
- 5 points calibration (MW151 MAX)

The innovative line of Milwaukee MAX portable meters includes a lot of new features:

- IP67 waterproof casing
- pH extended range: -2.00 to 20.00 pH, -2.000 to 20.000 pH (MW106 MAX)
- Up to 5-point calibration with 7 standard calibration buffers and two custom buffers
- Micro USB to connect a computer for file export
- Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time
- Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots)
- Electrode diagnostics feature checks and displays the condition of the pH electrode



The new Milwaukee MAX continuous monitors with 3 LCDs include a lot of new features:

- Easy Manual Calibration
- No Buttons to Program
- No Waiting for Software Confirmation
- Easy Wall Bracket Set-up (Brackets Included)
- Backlit LCD
- Two Point pH Calibration
- One Point TDS Calibration
- Replaceable pH Electrode
- "Easy Switch" TDS Conversion Technology Between 0.5 and 0.7

Measuring pH in cheese

Using MW101 PRO pH portable meter with a MA920B/1 pH electrode for measuring pH in cheese. During the cheese making process, the pH is measured multiple times. Each type of cheese may have a slightly different process and pH level. It is important for manufacturers and companies to be aware of the differences and treat each cheese variety with the quality and care it deserves. Measuring the pH of cheese essentially gives the manufacturer control of the cheese process.



MAX Dissolved oxygen and temperature portable meter

MW605 MAX is a portable, IP67 rated meter designed for fresh and saltwater measurements of dissolved oxygen (DO).

The **MW605 MAX** meter is compatible with **MA860** galvanic DO probe. Galvanic probes require no conditioning and thus the instrument is ready to measure when it is powered on. Concentration measurements are automatically compensated for temperature and salinity. Temperature is automatically measured (in both degree Celsius and Fahrenheit) and compensated. Salinity and altitude can be configured in Setup.

Other features include:

- IP67 waterproof casing
- Auto-off feature to prolong battery life
- One or two % saturation calibration points at 100% (water saturated air) and 0% (zero oxygen solution)
- Dedicated GLP key to store and recall data on system status
- Available log space for up to 1000 records
- Logged data can be exported using a USB cable



MAX Combined pH/EC/TDS/Temp portable meters

MW805 MAX and **MW806 MAX** portable meters combine the main features of a benchtop unit into a portable, water-resistant meter that can measure up to 4 different parameters — pH, EC (Conductivity), TDS (Total Dissolved Solids), and temperature.

- IP67 waterproof casing
- Easy to read LCD display
- Auto-off feature to prolong battery life
- Internal clock and date to keep track of time-dependent functions (calibration timestamp, calibration time out)
- Up to 5-point pH calibration (selection from 7 standard calibration buffers and 2 custom buffers)
- Automatically (ATC) or manually temperature compensated (MTC) measurements, with a user-selectable compensation coefficient
- Available log space for up to 1000 records
- Logged data can be exported using a micro USB cable
- Dedicated GLP key to store and recall data on system status

MAX pH/ORP/EC/TDS/NaCl/Temp bench meter

MW180 MAX is a compact and versatile bench meter with a user-friendly interface that can measure six different parameters – pH, ORP, EC, TDS (Total Dissolved Solids), percentage of salinity (NaCl%) and temperature – when paired with the respective probe.

pH calibration can be performed in up to 5-point (selectable between 7 standard calibration buffers and two custom buffers), to improve measurement reliability even when testing samples with wide differences in pH.

The auto-ranging feature for both EC and TDS measurements automatically sets the most suitable resolution for the tested sample. All measurements can be automatically (ATC) or manually temperature compensated (MTC) with a user-selectable compensation coefficient. The temperature compensation can be disabled if the actual conductivity value is required (No TC).

MW180 MAX has GLP data review and the data can be transferred to a PC through a USB port.

A unique device identity code protects against the risks of loss and misuse.



Looking for research grade
Look no further than Milwaukee. Our
top meters provide an affordable solution for
pH · ORP · EC · T




Are instruments on a budget? Our new high performance Bench- solution to your measuring needs. TDS · Temp · DO

- MW150 MAX: pH/ORP/Temp bench meter
- MW151 MAX: pH/ORP/Temp bench meter with logging
- MW160 MAX: pH/ORP/ISE/Temp bench meter with logging
- MW170 MAX: Autoranging EC/TDS/NaCl/Temperature laboratory bench meter
- MW180 MAX: pH/ORP/EC/TDS/NaCl/Temperature combination bench meter
- MW190 MAX: Extended range dissolved oxygen meter

Key features:

Built in rechargeable battery with 8 hours battery life supplied complete with battery charger, sensors, calibration solutions, electrode holder ready for use.




Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time.
Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots).

Electrode diagnostics feature checks and displays the condition of the pH electrode



2 USB ports: Standard USB socket to export data directly to a flash drive and micro USB to connect a computer for file export

Custom dual level LCD: Large and easy-to-read Custom dual level LCD with simultaneous readings and with user-friendly icons.



The complete Milwaukee sensor portfolio covers the whole scope of pH applications. These range from routine measurements to specific applications. To find your perfect match, go to page 58 – Electrode Selection Guide.

MW150 MAX

pH/ORP/Temperature Laboratory Bench Meter

- Years warranty 3
- MEM
- ATC
- MTC
- Points 3
- Dual Display
- Self diagnostics
- Memorized buffers 7
- CE
- GLP



MW150 MAX is an advanced pH/ORP/Temp microprocessor-based bench meter. It is ideal for students and technicians who need fast and reliable measurements.

This meter is provided with a series of new diagnostic features which add an entirely new dimension to the measurement of pH, by allowing the user to dramatically improve the reliability of the measurement:

- Up to 3-point automatic calibration with 7 standard calibration buffers
- Automatic or manual temperature compensation
- Built-in rechargeable battery with 8 hours battery life
- Auto-off feature to preserve battery energy
- Battery charger with battery monitor
- Dedicated GLP key
- Alphanumeric LCD displayed messages for user friendly, intuitive information/warning/error messages
- Internal clock and date to keep track of different time-dependent functions (calibration, timestamp, calibration time out)

Specifications	MW150 MAX	
Range	pH	-2.00 to 20.00 pH
	mV	±2000.0 mV
	Temp	-20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	pH	0.01 pH
	mV	0.1 mV
	Temp	0.1°C / 0.1°F
Accuracy (@25°C / 77°F)	pH	±0.01 pH
	mV	±1 mV
	Temp	±0.4°C / ±0.8°F
pH Calibration	up to 3-point automatic pH calibration, 7 standard calibration buffers (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01 and 12.45), no custom buffers	
Temperature Compensation	automatic from -20.0 to 120.0°C / -4.0 to 248.0°F or manual, without temperature probe	
pH Electrode	MA917B/1 (included)	
Temperature Probe	MA831R (included)	
Power Supply	12 VDC adapter (included)	
Battery life	8 hours	
Auto-off	5, 10, 30, 60 minutes or off	
Environment	0 to 50 °C; max RH 95%	
Packaging dimensions	335 x 120 x 255 mm	
Packaging weight	2 kg	

Ordering Information:



Accessories

- | | |
|--|--|
| <p>MA9001 pH 1.68 buffer solution, 230 mL bottle</p> <p>MA9004 pH 4.01 buffer solution, 230 mL bottle</p> <p>MA9006 pH 6.86 buffer solution, 230 mL bottle</p> <p>MA9007 pH 7.01 buffer solution, 230 mL bottle</p> <p>MA9009 pH 9.18 buffer solution, 230 mL bottle</p> <p>MA9010 pH 10.01 buffer solution, 230 mL bottle</p> <p>MA9011 Refilling Electrolyte Solution 3.5M KCl for pH/ORP electrodes, 230 mL</p> <p>MA9012 Refilling Electrolyte Solution 1M KNO₃, 230 mL, food applications</p> <p>MA9015 Electrode storage solution, 230 mL bottle</p> | <p>MA9016 Electrode cleaning solution, 230 mL bottle</p> <p>MA9112 pH 12.45 buffer solution, 230 mL bottle</p> <p>MA9310 12 VDC Adapter, 220 V</p> <p>MA9311 12 VDC Adapter, 110 V</p> <p>MA9315 Electrode Holder</p> <p>MA917B/1 Glass body, double junction refillable pH electrode</p> <p>MA831R Temperature probe</p> |
|--|--|


- MW150 MAX** is supplied complete with:
- MA917B/1 Double junction refillable pH electrode
 - MA831R Temperature Probe
 - MA9315 Electrode Holder
 - M10004 pH 4.01 Sachet Buffer Solution
 - M10007 pH 7.01 Sachet Buffer Solution
 - M10010 pH 10.01 Sachet Buffer Solution
 - M10016 Sachet Electrode Cleaning Solution
 - MA9310 12 VDC Adapter
 - Graduated pipette
 - Instruction manual

MW151 MAX

pH/ORP/Temperature Logging Laboratory Bench Meter

This high performance microprocessor-based pH/ORP/Temp Bench meter is an ideal tool in schools, laboratories and production plants. It is provided with a series of new diagnostic features which add an entirely new dimension to the measurement of pH, by allowing the user to dramatically improve the reliability of the measurement:

- Up to 5-point calibration with 7 standard calibration buffers and two custom buffers
- 2 USB ports: Standard USB socket to export data directly to a flash drive and micro USB to connect a computer for file export
- Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time
- Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots)
- Electrode diagnostics feature checks and displays the condition of the pH electrode
- Built-in rechargeable battery with 8 hours battery life
- Battery charger with battery monitor
- Dedicated GLP key
- Alphanumeric LCD displayed messages for user friendly, intuitive information/warning/ error messages



- Years warranty **3**
- LOG**
- ATC
- MTC
- Points **5**
- Dual Display
- Self diagnostics
- Memorized buffers **7**
- CE**
- USB**
- GLP**

Specifications	MW151 MAX
Range	pH -2.00 to 20.00 pH / -2.000 to 20.000 pH mV ±2000.0 mV Temp -20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	pH 0.01 pH / 0.001 pH mV 0.1 mV Temp 0.1°C / 0.1°F
Accuracy (@25°C)	pH ±0.01 pH / ±0.002 pH mV ±1 mV Temp ±0.4°C / ±0.8°F
pH Calibration	up to 5-point automatic pH calibration, 7 standard calibration buffers (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01 and 12.45) and two custom buffers
Temperature Compensation	automatic from -20.0 to 120.0°C / -4.0 to 248.0°F or manual, without temperature probe
pH Electrode	MA917B/1 (included)
Temperature Probe	MA831R (included)
Log	Maximum 1000 records; On demand, 200 samples; On stability, 200 samples Interval logging, 600 samples (max. 100 lots)
PC connectivity	1 USB port, 1 micro USB port
Power Supply	12 VDC adapter (included), 5 VDC USB adapter
Battery life	8 hours
Auto-off	5, 10, 30, 60 minutes or off
Environment	0 to 50 °C; max RH 95%
Packaging dimensions	335 x 120 x 255 mm
Packaging weight	2 kg

Ordering Information:



Accessories

- | | |
|--|---|
| MA9001 pH 1.68 buffer solution, 230 mL bottle | MA831R Temperature probe |
| MA9004 pH 4.01 buffer solution, 230 mL bottle | MA9112 pH 12.45 buffer solution, 230 mL bottle |
| MA9006 pH 6.86 buffer solution, 230 mL bottle | MA9310 12 VDC Adapter, 220 V |
| MA9007 pH 7.01 buffer solution, 230 mL bottle | MA9311 12 VDC Adapter, 110 V |
| MA9009 pH 9.18 buffer solution, 230 mL bottle | MA9315 Electrode Holder |
| MA9010 pH 10.01 buffer solution, 230 mL bottle | MA917B/1 Glass body, double junction refillable pH electrode |
| MA9011 Refilling Electrolyte Solution 3.5M KCl for pH/ORP electrodes, 230 mL | MA924B/1 ±2000 mV Glass ORP electrode, refillable with BNC connector and 1 meter cable |
| MA9012 Refilling Electrolyte Solution 1M KNO ₃ , 230 mL, food applications | |
| MA9015 Electrode storage solution, 230 mL | |
| MA9016 Electrode cleaning solution, 230 mL | |

- MW151 MAX is supplied complete with:
- MA917B/1 Double junction refillable pH electrode
 - MA831R Temperature Probe
 - MA9315 Electrode Holder
 - M10004 pH 4.01 Sachet Buffer Solution
 - M10007 pH 7.01 Sachet Buffer Solution
 - M10010 pH 10.01 Sachet Buffer Solution
 - M10016 Sachet Electrode Cleaning Solution
 - MA9310 12 VDC Adapter
 - Graduated pipette
 - USB cable
 - Instruction manual

MW160 MAX

pH/ORP/ISE/Temperature Laboratory Bench Meter

- Years warranty 3
- MEM
- ATC
- MTC
- Points 3
- Dual Display
- Self diagnostics
- Memorized buffers 7
- CE
- GLP



MW160 is a compact and versatile bench meter that can measure up to four different parameters — pH, ORP, ISE (directly in ppm) and temperature. The main operating modes are setup, calibration, measurement and logging. pH calibration can be performed in up to 3 points (using a selection of 7 standard calibration buffers), to improve measurement reliability, even when testing samples with wide differences in pH. ISE calibration can be performed in up to 2 points with 6 standard solutions available. The meter can store up to 50 data sets for each range (pH, ORP, ISE) that can be downloaded to a PC via RS232 or USB.

Other features include:

- Easy to read LCD display
- Relative mV feature
- Internal clock and date to keep track of different time-dependent functions (calibration timestamp, calibration time-out)
- User-selectable time-out alarm to alert the user that too much time elapsed since the last pH calibration
- GLP feature to recall last calibration data for pH and ISE

For accurate measurements use the electrode holder supplied with the meter.

Specifications	MW160 MAX
Range	pH -2.00 to 16.00 pH mV ±699.9 mV / ±2000.0 mV ISE 0.001 to 19999 ppm Temp -20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	pH 0.01 pH mV 0.1 mV / 1 mV ISE 0.001 ppm, 0.01 ppm, 0.1 ppm, 1 ppm Temp 0.1°C / 0.1°F
Accuracy (@20°C / 68°F)	pH ±0.01 pH mV ±0.2 mV / ±1 mV ISE ±0.5% Full scale Temp ±0.4°C / ±0.8°F
Relative mV offset	±2000 mV
pH Calibration	up to 3-point pH calibration, with 7 memorized buffers (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01 and 12.45)
ISE calibration	1 or 2 points calibration, 6 standard solutions available: 0.01, 0.1, 1, 10, 100, 1000 ppm
Temperature Compensation	automatic from -20.0 to 120.0°C / -4.0 to 248.0°F or manual, without temperature probe
pH Electrode	MA917B/1 (included)
Temperature Probe	MA831R (included)
Logging memory	Up to 50 records for each measurement range (pH, ORP, ISE)
Power Supply	12 VDC adapter (included)
PC connectivity	USB port and RS232 interface
Environment	0 to 50 °C; max RH 95%
Packaging dimensions	335 x 120 x 255 mm
Packaging weight	2.55 kg

Ordering Information:



- MW160 MAX** is supplied complete with:
- **MA917B/1** Double junction refillable pH electrode
 - **MA831R** Stainless steel temperature probe
 - **M10004B** pH 4.01 buffer solution (sachet)
 - **M10007B** pH 7.01 buffer solution (sachet)
 - **M10010B** pH 10.01 buffer solution (sachet)
 - **M10016B** Electrode cleaning solution (sachet)
 - **MA9315** Electrode holder
 - **MA9350** RS232 connector cable (2 m)
 - Graduated pipette
 - 12 VDC adapter
 - Instrument quality certificate
 - Instruction manual

Accessories

- | | |
|--|---|
| MA9004 pH 4.01 buffer solution, 230 mL bottle | MA9310 12 VDC Adapter, 220 V |
| MA9007 pH 7.01 buffer solution, 230 mL bottle | MA9311 12 VDC Adapter, 110 V |
| MA9010 pH 10.01 buffer solution, 230 mL bottle | MA9315 Electrode Holder |
| MA9015 Electrode storage solution, 230 mL bottle | MA917B/1 Glass body, double junction refillable pH electrode |
| MA9016 Electrode cleaning solution, 230 mL bottle | MA924B/1 Glass ORP electrode |
| MA9112 pH 12.45 buffer solution, 230 mL bottle | MA831R Temperature probe |
| | SE300 Platinum ORP electrode |



pH Electrode basics




pH electrodes are constructed from a special composition glass which senses the hydrogen ion concentration. This glass is typically composed of alkali metal ions. The alkali metal ions of the glass and the hydrogen ions in solution undergo an ion exchange reaction, generating a potential difference. In a combination pH electrode, the most widely used variety, there are actually two electrodes in one body. One portion is called the measuring electrode, the other the reference electrode. The potential generated at the junction site of the measuring portion is due to the free hydrogen ions present in solution.


The potential of the reference portion is produced by the internal element in contact with the reference fill solution. This potential is always constant. In summary, the measuring electrode delivers a varying voltage and the reference electrode delivers a constant voltage to the meter. The voltage signal produced by the pH electrode is a very small, high impedance signal. The input impedance requires to be interfaced only with equipment with high impedance circuits.

Milwaukee has a wide assortment of pH and ORP electrodes to meet all your specific requirements. Finding the right electrode for a specific application is a very important task and in order to solve this selection problem it is important to consider the following:

- Glass body electrode versus Epoxy (plastic) body electrode:** Glass body electrodes stand higher temperatures (typically 100°C against 80°C for plastic) and are more resistant to corrosive chemicals and solvents. They are easier to clean and are available in different shapes depending on the application. On the other hand plastic body electrodes are more rugged and the glass bulb is better protected.
- Gel filled electrodes versus refillable electrodes:** refillable electrodes last longer since electrolyte can be changed for repeated usage. The response is faster due to a greater outflow of electrolyte into the sample and therefore less likely to clog. Gel filled electrodes require less maintenance and resist to higher pressure.
- Double reference junction versus Single junction reference:** Double junction reference electrodes have a longer life and protects the sample measured from silver contamination from the electrolyte. The Silver wire is more protected and therefore gets less contaminated. The single junction electrodes normally cost less and are ideal for general purpose applications.
- Conic shaped versus Sphere shaped:** The conic-shaped electrode is easier to clean and to maintain (ideal for applications such as dairy). Has a more rugged tip and therefore ideal for penetration. The sphere-shaped has a faster response time due to the larger surface area on the bulb.




Model	MA919B/1	MA924B/1
Measuring Range	0 to 12 pH	±2000 mV
Temperature Range	-5 to 70 °C	0 to 70 °C
Shaft material	glass	glass
Reference Electrolyte	KCL 3.5M	KCL 3.5M
Reference Junction	open	open
Reference Type	double Ag/AgCl	double Ag/AgCl
Shape of membrane	spheric	Platinum ring
Max. Pressure	0,1 bar	0,1 bar
Connector type	BNC	BNC
Cable length	coaxial 1 meter	coaxial 1 meter
Shaft length	120 mm	120 mm
Diameter	8 mm	8 mm
Application	food laboratory	food laboratory



The pH electrode, due to the nature of its construction, needs to be kept moist at all times. In order to operate properly, glass needs to be hydrated. Hydration is required for the ion exchange process to occur. If an electrode should become dry, it is best to place it in some tap water for half an hour to condition the glass.

pH electrodes are like batteries; they run down with time and use. As an electrode ages, its glass changes resistance. This resistance change alters the electrode potential. For this reason, electrodes need to be calibrated on a regular basis. Calibration in pH buffer solution corrects for this change. Calibration of any pH equipment should always begin with buffer 7.0 as this is the "zero point." The pH scale has an equivalent mV scale. The mV scale ranges from +420 to -420 mV. At a pH of 7.0 the mV value is 0. Each pH change corresponds to a change of approx. ± 60 mV. As pH values become more acidic the mV values become greater.

pH electrodes have junctions which allow the internal electrolyte solution of the measuring electrode to leak out into the solution being measured.




Model	MA916B/1 - MA916B/3	MA917B/1	MA918B/1
Measuring Range	0 to 12 pH	0 to 14 pH	0 to 12 pH
Temperature Range	0 to 60°C	0 to 70°C	-5 to 60°C
Shaft Material	glass	glass	glass
Reference Electrolyte	KCl 3.5M	KCl 3.5M	KCl 3.5M
Reference Junction	ceramic, single	ceramic, single	ceramic, triple
Reference Type	double, Ag/AgCl	double, Ag/AgCl	double, Ag/AgCl
Shape of membrane	spheric	spheric	conic
Max pressure	0.1 bar	0.1 bar	0.1 bar
Connector Type	BNC	BNC	BNC
Cable length	coaxial, 1 or 3 m	coaxial, 1 m	coaxial, 1 m
Shaft length	120 mm	120 mm	120 mm
Diameter	12 mm	12 mm	12 mm
Application	laboratory applications	laboratory applications	food-laboratory applications

pH Electrode basics


This junction can become clogged by particulates in the solution and can also facilitate poisoning by metal ions present in the solution. If a clogged junction is suspected it is best to soak the electrode in tap water to dissolve the material and clear the junction. When not in use it is best to store the electrode in either buffer 4.0 or buffer 7.0. Never store an electrode in distilled or deionized water as this will cause migration of the electrolyte solution from the electrode.

How long a pH electrode will last will depend on how it is cared for and the solutions it is used to measure. Typically, a gel-filled combination pH electrode will last six months to 1 year depending on the care and application.

How long an electrode will last is determined by how well the probe is maintained and the pH application. The harsher the system, the shorter the lifespan. For this reason it is always a good idea to have a back-up electrode on hand to avoid any system down time. Calibration is also an important part of electrode maintenance. This assures not only that the electrode is behaving properly but that the system is operating correctly.




Electrode Storage Bottle Cap: All our pH and ORP electrodes are supplied with a bottle storage cap which helps to keep the glass bulb always wet.



Model	MA920B/1	MA991B/1	MA905B/3	MA925B/3
Measuring Range	0 to 12 pH	0 to 13 pH	0 to 13 pH	±2000 mV
Temperature Range	-5 to 50°C	-5 to 70°C	-10 to 80°C	-5 to 100°C
Shaft Material	PVDF	glass	PVDF	PVDF
Reference Electrolyte	Viscolene	gel	polymer	polymer
Reference Junction	open	ceramic, single	double PTFE	PTFE
Reference Type	single, Ag/AgCl	single, Ag/AgCl	double Ag/AgCl	Ag/AgCl
Shape of membrane	conic	spheric	flat	flat Pt sensor
Max pressure	0.1 bar	0.1 bar	6 bar	6 bar
Connector Type	BNC	BNC	3/4" NPT - BNC	BNC
Cable length	coaxial, 1 m	coaxial, 1 m	3 m	3 meter
Shaft length	75 mm	120 mm	120 mm	135 mm
Diameter	6 mm	12 mm	22 mm	22 mm
Application	food-laboratory applications	laboratory applications	industrial applications	industrial applications




DIN Connector



BNC Connector

Temperature compensation: When measuring pH using a pH electrode the temperature error from the electrode varies based on the Nernst Equation as 0.03 pH/10C/unit of pH away from pH7. The error due to temperature is a function of both temperature and the pH being measured. Temperature compensation can be achieved manually or automatically. Manual temperature compensation is usually achieved by entering the temperature of the fluid being measured into the instruments menu and then the instrument will display a "Temperature Compensated" pH reading.


This means that the temperature is corrected to the value expected at 25 °C. Automatic temperature compensation requires input from a temperature sensor and constantly sends a compensated pH signal to the display. Automatic temperature compensation is useful for measuring pH in systems with wide variations in temperature.



Model	MA913B/3 - B/5	MA923B/3 - B/5	SE-220	SE-300
Measuring Range	0 to 13 pH	±1999 mV	0 to 13 pH	±1999 mV
Temperature Range	20 to 60°C	20 to 60°C	-5 to 70 °C	20 to 60°C
Shaft Material	PEI	PEI	PEI	PEI
Reference Electrolyte	gel	gel	gel	gel
Reference Junction	ceramic, single	cloth	cloth	cloth
Reference Type	single, Ag/AgCl	single, Ag/AgCl	double Ag/AgCl	double, Ag/AgCl
Shape of membrane	spheric	spheric, platinum sensor	spheric	spheric, platinum sensor
Max pressure	2 bar	2 bar	2 bar	2 bar
Connector Type	BNC	BNC	BNC	BNC
Cable length	coaxial, 3 m or 5 m	7-pole, 3 m or 5 m	coaxial 1 meter	7-pole, 3 m or 5 m
Shaft length	120 mm	120 mm	120 mm	120 mm
Diameter	12 mm	12 mm	12 mm	12 mm
Application	swimming pool	swimming pool	drinking water, waste water	drinking water, waste water

pH Electrode

Storage and Maintenance



pH Electrode Storage and Maintenance

To ensure a quick response and free-flowing liquid junction, the sensing element and reference junction must not be allowed to dry out. For refillable electrodes make sure that the refill hole is open when measuring to ensure that the electrolyte solution flows properly through the reference junction

Routine Storage

Soak electrode in a pH Electrode Storage Solution (MA9015). If a storage solution is unavailable, pH 4 buffer or pH7.01 may be used. When not in use, the fill hole should be covered to prohibit evaporation of reference fill solution.

Maintenance & Cleaning

Cleaning your electrode between and after use will help extend the life of your electrode and avoid the cost of early replacement. Soak electrode in MA9016 cleaning solution for half an hour, followed by soaking it in storage solution (MA9015) for at least two hours. For long term storage, always keep the electrode in a bottle, filled with sufficient storage solution to cover the bulb and the junction.

Weekly Maintenance

Inspect electrodes for scratches, cracks, salt crystal buildup, or membrane/junction deposits. Rinse off any salt buildup with distilled water, and remove any membrane/junction deposits.

Normal aging


As pH electrodes age their efficiency is reduced. The aging is usually caused either by contamination of the glass membrane (which loses its sensitivity) or by blockage of the reference junction. The lifespan of the pH electrode is 6 months to 1 year (under normal conditions).

Get accurate pH readings

The pH electrode is the most sensitive component of your pH instrument. Correct calibration procedures combined with proper maintenance will provide reliable measurements.

Calibration: The electrode must be calibrated regularly to ensure accurate, repeatable measurements. Although one-point calibration suffices for fairly reliable measurements, two or even three-point calibrations will give you more accurate results across the entire measurement range.

pH readings are only as accurate as the solution used for calibration. For high accuracy it is important to use uncontaminated buffers. Our 20 ml sachets always ensure a fresh solution and calibration can be performed directly in the sachet. Our 230 ml bottles are easy to use and reduce risk of contamination opposed to bigger bottles.



The calibration curve

MW105 MAX

Portable pH/ORP/Temp Meter

- Years warranty **3**
- ATC
- Points **2**
- Dual Display
- Self diagnostics
- CE
- IP **67**
- GLP



The Milwaukee **MW105 MAX** meter combines all the features of a benchtop unit into a portable, IP67 rated meter. The instruments are provided with a series of new diagnostic features for improved pH measurement reliability:

- IP67 waterproof casing
- pH extended range: -2.00 to 20.00 pH
- up to 3-point automatic pH calibration, 7 standard calibration buffers (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01 and 12.45)
- alphanumeric LCD displayed messages for user friendly, intuitive information / warning / error messages
- auto-off feature to preserve battery life
- internal clock and date to keep track of different time-dependent functions (calibration timestamp, calibration time out)
- dedicated GLP key

Hard Carrying Case

Each meter is supplied in a hard carrying case ideal for field measurements.



Specifications	MW105 MAX	
Range	pH	-2.00 to 20.00 pH
	mV	±2000 mV
	Temp*	-20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	pH	0.01 pH
	mV	1 mV
	Temp	0.1°C / 0.1°F
Accuracy (@25°C / 77°F)	pH	±0.02 pH
	mV	±1 mV
	Temp	±0.5°C up to 60°C; ±1°C outside / ±1°F up to 140°F; ±2°F outside automatic, up to 3 points calibration, 7 standard buffers available (1.68, 4.01, 6.86, 7.01, 9.18, 10.01, 12.45)
pH Calibration	factory calibrated	
ORP calibration	automatic, from -5 to 80 °C (-23 to 176 °F); manual	
Temperature compensation	automatic, from -5 to 80 °C (-23 to 176 °F); manual	
Probe	MA906BR/1 amplified pH/temperature probe (supplied)	
Temperature probe	Built-in temperature probe	
Input impedance	10 ¹² Ohm	
Battery Type	3 x 1.5V alkaline AA (included)	
Battery Life	Approx. 200 hours of use	
Environment	0 to 50°C / 32 to 122°F; max RH 95%	
Auto-off	5, 10, 30, 60 minutes or off	
Packaging dimensions	305 x 280 x 115 mm	
Packaging weight	1.22 kg	

* Temperature range is limited to 80.0 °C, when using the MA906BR/1 probe

Calibration, Maintenance & Cleaning Solutions

Choose from our wide selection of calibration, maintenance and cleaning solutions at page 59.



Ordering Information

MW105 MAX is supplied complete with:

- **MA906BR/1** amplified pH/temperature probe
- **M10004** pH 4.01 buffer solution (20 mL sachet)
- **M10007** pH 7.01 buffer solution (20 mL sachet)
- **M10010** pH 10.01 buffer solution (20 mL sachet)
- **M10016** electrode cleaning solution (20 mL sachet)
- Graduated pipette
- 1.5V alkaline AA battery (3 pcs.)
- Instrument quality certificate
- Instruction manual

Accessories

- MA906BR/1** amplified pH/temperature probe
- M10000B** Electrode rinse solution, 20 mL (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)

- M10010B** pH 10.01 buffer solution, 20 mL sachet (25 pcs)
- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9006** pH 6.86 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle
- MA9009** pH 9.18 buffer solution, 230 mL bottle
- MA9010** pH 10.01 buffer solution, 230 mL bottle
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL



MW106 MAX

Portable pH/ORP/Temp Meter

The Milwaukee **MW106 MAX** meter combines all the features of a benchtop unit into a portable, IP67 rated meter. The instruments are provided with a series of new diagnostic features for improved pH measurement reliability:

- IP67 waterproof casing
- pH extended range: -2.00 to 20.00 pH / -2.000 to 20.000 pH
- up to 5-point automatic pH calibration, 7 standard calibration buffers (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01 and 12.45) and two custom buffers
- available log space for up to 1000 records
- alphanumeric LCD displayed messages for user friendly, intuitive information / warning / error messages
- auto-off feature to preserve battery life
- internal clock and date to keep track of different time-dependent functions (calibration timestamp, calibration time out)
- dedicated GLP key

Calibration, Maintenance & Cleaning Solutions

See page 59.



- Years warranty 3
- ATG
- Points 2
- Dual Display
- Self diagnostics
- CE
- IP67
- GLP
- USB
- LOG

Specifications	MW106 MAX
Range	pH -2.00 to 20.00 pH / -2.000 to 20.000 pH mV ±2000 mV Temp* -20.0 to 120.0 °C (-4.0 to 248.0 °F)
Resolution	pH 0.01 pH / 0.001 pH mV 0.1 mV Temp 0.1°C / 0.1°F
Accuracy (@25°C)	pH ±0.01 pH / ±0.002 pH mV ±1 mV Temp ±0.5°C up to 60°C; ±1°C outside / ±1°F up to 140°F; ±2°F outside
pH Calibration	automatic, up to 5 points calibration, 7 standard buffers available (1.68, 4.01, 6.86, 7.01, 9.18, 10.01, 12.45) and two custom buffers
ORP Calibration	factory calibrated
Temperature Compensation	automatic, from -5 to 80°C / 23 to 176°F
Probe	MA906BR/1 amplified pH/temperature probe (supplied)
Temperature probe	Built-in temperature probe
Input impedance	10 ¹² Ohm
Log	Max. 1000 log records (stored in up to 100 lots) On demand, 200 logs / On stability, 200 logs / Interval logging, 1000 logs
PC connectivity	1 micro USB port
Battery Type	3 x 1.5V alkaline AA (included)
Battery Life	approx. 200 hours of use
Auto-off	5, 10, 30, 60 minutes or off
Environment	0 to 50°C ; 95% RH
Packaging dimensions	305 x 280 x 115 mm
Packaging weight	1.22 kg

* Temperature range is limited to 80.0 °C, when using the MA906BR/1 probe

Hard Carrying Case

Each meter is supplied in a hard carrying case ideal for field measurements.



Accessories

- MA906BR/1** amplified pH/temperature probe
- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)

- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)
- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL



Ordering Information

- MW106 MAX** is supplied complete with:
- **MA906BR/1** amplified pH/temperature probe
 - **M10004** pH 4.01 buffer solution (20 mL sachet)
 - **M10007** pH 7.01 buffer solution (20 mL sachet)
 - **M10010** pH 10.01 buffer solution (20 mL sachet)
 - **M10016** electrode cleaning solution (20 mL sachet)
 - Graduated pipette
 - 1.5V alkaline AA battery (3 pcs.)
 - USB cable
 - Instrument quality certificate
 - Instruction manual

MW100 PRO/MW101 PRO/MW102 PRO+/MW500 PRO

Budget pH/ORP/Temperature Portable Meters for fast and reliable results

- ATC
- MTC
- Points 2
- Self diagnostics
- CE







MW100 PRO, MW101 PRO, MW102 PRO+ and MW500 PRO are compact microprocessor-based pH, ORP and Temperature Portable Meters. These handy and ergonomically designed portable meters are ideal for anyone working on a low budget and still requires fast and reliable measurements.

These portable meters are suitable for a wide range of applications, such as Educational, Agriculture and Horticulture, as well as water and environmental analysis. These easy and fast to calibrate portable meters have a small, ergonomic and light case design. Other features include large and easy to read LCD and long battery life.

All meters are supplied with pH or ORP electrodes and calibration solutions in a carton box.

- **MW100 PRO** performs pH measurements with a 0.1 pH resolution.
- **MW101 PRO** performs pH measurements with a 0.01 pH resolution and with manual temperature compensation.
- **MW102 PRO+** is a microprocessor based pH/Temperature meter with extended range (-2.00 to 16.00 pH), Automatic Temperature Compensation, automatic calibration in 2 points and ± 0.02 pH accuracy.
- **MW500 PRO** performs ORP measurements with a range of ± 1000 mV.

Specifications		 MW100 PRO pH Meter	 MW101 PRO pH Meter	 MW102 PRO+ pH/Temp Meter	 MW500 PRO ORP Meter
Range	pH/ORP Temp.	0.0 to 14.0 pH	0.00 to 14.00 pH	-2.00 to 16.00 pH -5 to 70°C	± 1000 mV
Resolution	pH/ORP Temp.	0.1 pH	0.01 pH	0.01 pH 0.1°C	1 mV
Accuracy (@25°C)	pH/ORP Temp.	± 0.2 pH	± 0.02 pH	± 0.02 pH $\pm 0.5^\circ\text{C}$	± 5 mV
Typical EMC Deviation	pH Temp.			± 0.02 pH $\pm 0.5^\circ\text{C}$	
Temperature Compensation		N.A.	manual, 0 to 50°C	automatic, 0 to 70°C	
Calibration		manual, 2-point through offset and slope trimmers	manual, 2-point through offset and slope trimmers	automatic at 1 or 2 points with memorized buffers (pH 4.01, 7.01, 10.01)	
pH Electrode		SE220 (included)	SE220 (included)	SE220 (included)	SE300 (included)
ORP Electrode					
Temperature Probe				MA831R (included)	
Environment		0 to 50°C, max RH 95%	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%
Battery Type		1 x 9V alkaline (included)	1 x 9V alkaline (included)	1 x 9V alkaline (included)	1 x 9V alkaline (included)
Battery Life		approx. 300 hours of use	approx. 300 hours of use	approx. 300 hours of use	approx. 300 hours of use
Auto-off				after 8 minutes of non-use	
Packaging dimensions		212 x 145 x 67 mm	212 x 145 x 67 mm	212 x 145 x 67 mm	212 x 145 x 67 mm
Packaging weight		440 g	420 g	500 g	400 g

Accessories

- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)
- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle

- MA9010** pH 10.01 buffer solution, 230 mL
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL
- MA831R** Temperature probe
- MA9020** 200-275 mV ORP solution, 230 mL
- SE220** pH electrode with BNC connector and 1 m cable
- SE300** Platinum ORP electrode with 1 m cable



Ordering Information

MW100 PRO and **MW101 PRO** are supplied complete with a SE220 pH electrode, pH 7.01 20 mL sachet of calibration solution, calibration screwdriver, 9V battery and instructions.

MW102 PRO+ is supplied complete with a SE220 pH electrode, MA831R stainless steel temperature probe, pH 4.01 and pH 7.01 20 mL sachet of calibration solution, 9V battery and instructions.

MW500 PRO is supplied complete with a SE300 platinum electrode, 9V battery and instructions.

Measuring pH in soil

Using MW101 PRO pH Portable Meter with a MA920B/1 pH Electrode for measuring pH in SOIL

pH is a measure of the activity of the hydrogen ion (H⁺) in the soil solution. If the concentration of H⁺ is high, the medium is said to be acid. If it is low, it is said to be alkaline. Most agricultural soils are found between the range of 4 to 10 (when measured in water).

For practical purposes, soil is neutral when pH is between 6 to 8, depending on plant requirements, and it is acidic when pH is less than 6 and alkaline when it is greater than 8.



1. Collect samples of soil.
Take samples from a homogeneous area per 1000m². In smaller places it is also suggested to take at least two samples (the more samples, the more accurate the measurement will be). Don't take samples from soil where are obvious disorders.

Amount of sample:
Use the same amount of soil for every sample (for example: use identical size sachets)



Spot of sample:
General: take the top 5 cm of the ground
Annuals: from 20-40 cm deep
Fruits: from 20-60 cm deep

Spread the soil on a paper and let it dry out in a shaded place, or put it into a 40°C oven.



2. Shred the dry soil and mix the samples.
You will get a homogeneous sample. It mustn't contain rocks or organic residues. Take a sample from this mixture for the measurement.



3. Sift the soil through a 2 mm sifter.

4. Weigh out 1 unit soil (100 g is recommended) and put 2 unit (200 g, 2 dl) distilled water to it.



5. Stir it for 30 seconds.
Wait about five minutes.



6. Stir it again then measure the pH of the solution.



Measuring pH in cheese

Using MW101 PRO pH portable meter with a MA920B/1 pH electrode for measuring pH in cheese

The quality of cheese flavor and texture is the result of well-kept pH and temperature. pH makes sure quality standards have been met; in doing so, they are guaranteeing the safety of the cheese production. Most cheeses range from 5.1 to 5.9 in pH. However, this range will have exceptions to certain types of cheeses such as Camembert cheese which has a pH of 7.4.

During the cheese making process, the pH is measured multiple times. Each type of cheese may have a slightly different process and pH level. It is important for manufacturers and companies to be aware of the differences and treat each cheese variety with the quality and care it deserves. Measuring the pH of cheese essentially gives the manufacturer control of the cheese process.

Cheese making process:

For optimal measurement put a sample into a beaker




1. Addition of the starter culture (temperature should stay below 20°C)
pH level (rennet-induced): 5.1 - 5.3
pH level (acid-induced): 4.



2. Coagulation (temperature 30°C)
Usually the pH level stay between: 5.35 – 5.45
In certain cases it can be as low as pH 4.



3. Pressing (room temperature: 16-18°C for mild cheeses and 25°C for hard cheeses)
pH will decrease (pH 5.0 – 5.3)



4. Brining in salt solution (temperature of solution: 15°C)
optimal pH level: 5.2
(except soft cheeses like Roquefort where the pH level should be kept at pH 4.7)

During ripening pH level will increase till the optimal ready value. See the table below



Optimal pH values of ready cheeses	
American, mild	4.98
Camembert	7.44
Cheddar	5.90
Cottage	4.75 - 5.02
Cream, Philadelphia	4.10 - 4.79
Dip	5.80
Edem	5.40
Old English	6.15
Roquefort	5.10 - 5.98
Parmesan	5.20 - 5.30
Snippy	5.18 - 5.21
Stilton	5.70
Swiss Gruyere	5.68 - 6.62

pH55 PRO/pH56 PRO

Compact, pocketable, waterproof pH/Temperature testers with replaceable electrode

Water-resistant pH testers with large dual-level LCD that displays pH and temperature (°C or °F). The large display shows readings in an extended range from -2.0 to 16.0 pH (pH56 has a 0.01 pH resolution) and simultaneously shows temperature from -5.0 to 60.0°C or 23.0 to 140.0°F. They have a stability indicator and hold function that freezes the display for easy and accurate recording. The large display also has graphic symbols to guide you through all operations.

Complete with a temperature probe for fast and more precise temperature measurement they compensate automatically for temperature. Calibration is made automatically in 1 or 2 points with memorized standard and NIST buffer sets. Auto power OFF saves battery power after non-use.

The double-junction electrode can be replaced in a very fast and simple way! The modular design allows easy electrode and battery replacement.

Specifications		pH55 PRO	pH56 PRO
Range	pH	-2.0 to 16.0 pH	-2.00 to 16.00 pH
	Temp.	-5.0 to 60.0°C / 23.0 to 140.0°F	-5.0 to 60.0°C / 23.0 to 140.0°F
Resolution	pH	0.1 pH	0.01 pH
	Temp.	0.1°C / 0.1°F	0.1°C / 0.1°F
Accuracy (@25°C)	pH	±0.1 pH	±0.05 pH
	Temp.	±0.5°C / ±1°F	±0.5°C / ±1°F
Typical EMC Deviation	pH	±0.1 pH	±0.02 pH
	Temp.	±0.3°C / ±0.6°F	±0.3°C / ±0.6°F
Calibration		automatic, 1 or 2 points with 2 sets of memorized buffers (pH 4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)	automatic, 1 or 2 points with 2 sets of memorized buffers (pH 4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)
Temperature Compensation		automatic from -5 to 60°C	automatic from -5 to 60°C
Probe		Mi56P (replaceable)	Mi56P (replaceable)
Environment		-5 to 50°C / 32 to 122°F; max RH 100%	-5 to 50°C / 32 to 122°F; max RH 100%
Battery Type		4 x 1.5V: IEC LR44, A76 (included)	4 x 1.5V: IEC LR44, A76 (included)
Battery Life		approx. 300 hours of use	approx. 300 hours of use
Auto-off		after 8 minutes of non-use	after 8 minutes of non-use
Packaging dimensions		254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight		200 g	200 g

Accessories

- | | |
|--|---|
| Mi56P Replaceable electrode for pH55 & pH56 | M10010B pH 10.01 buffer solution 20 mL sachet (25 pcs) |
| M10000B Electrode rinse solution, 20 mL sachet (25 pcs) | MA9004 pH 4.01 buffer, 230 mL bottle |
| M10004B pH 4.01 buffer solution 20 mL sachet (25 pcs) | MA9007 pH 7.01 buffer solution, 230 mL bottle |
| M10007B pH 7.01 buffer solution 20 mL sachet (25 pcs) | MA9010 pH 10.01 buffer solution, 230 mL bottle |
| | MA9015 Electrode storage solution, 230 mL |
| | MA9016 Electrode cleaning solution, 230 mL |
| | MA753 Hard carrying case for 2 testers |

Ordering Information

pH55 PRO and pH56 PRO is supplied complete in a carton box with protective cap, 20 mL pH 4.01 and pH 7.01 sachets of calibration solution.

Optionally pH55 PRO is also available in a kit (Mi5559 or Mi5560) together with EC59 PRO or EC60 PRO EC/TDS/Temp Meters.



- Years warranty 2
- ATC
- IP65
- Points 2
- AUTO Buffer
- Dual Display
- Self diagnostics
- CE
- Electrode Replaceable

pH/Temperature Sensor

The pH55 PRO and pH56 PRO's exposed temperature sensor provides fast response time, and its proximity to the pH electrode guarantees much more accurate temperature compensated readings.



Replaceable electrode

Replace the electrode in a fast and simple way yourself! Just unscrew the plastic ring on the top of the electrode and replace the electrode with a new one.



- 2 Years warranty
- ATC
- IP65
- 2 Points
- AUTO Buffer
- Dual Display
- Self diagnostics
- CE
- Electrode Replaceable



ORP57 PRO/pH58 MAX

Pocket-size pH/ORP/Temperature Meters with replaceable electrode

Combination water-resistant testers with advanced functions also include the model **pH58 MAX** for simultaneous pH and ORP measurements and temperature, which is continuously displayed on the dual level LCD. It shows readings in an extended range from -2.00 to 16.00 pH or ±1000 mV and simultaneously shows temperature from -5.0 to 105.0°C or 23 to 221°F.

The **pH58 MAX** has a stability indicator and hold feature that freezes the display for easy and accurate recording. The large display also has graphic symbols to guide you through all operations. Calibration is performed automatically at 1 or 2 points using standard or NIST buffers.

The modular design allows easy electrode and battery replacement.



Specifications	ORP57 PRO	pH58 MAX
Range	pH ORP ±1000 mV Temp. -5.0 to 60.0°C / 23.0 to 140.0°F	-2.00 to 16.00 pH ±1000 mV -5.0 to 60.0°C / 23.0 to 140.0°F
Resolution	pH 1 mV ORP 0.1°C / 0.1°F Temp.	0.01 pH 1 mV 0.1°C / 0.1°F
Accuracy (@25°C)	pH ±2 mV ORP ±0.5°C / ±1°F Temp.	±0.05 pH ±2 mV ±0.5°C / 1°F
Typical EMC Deviation	pH ±2 mV ORP ±0.3°C / ±0.6°F Temp.	±0.02 pH ±2 mV ±0.3°C / ±0.6°F
pH Calibration		automatic for pH, 1 or 2 points from -5 to 60°C with 2 sets of memorized buffers (pH 4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)
ORP Calibration	factory calibrated	factory calibrated
Probe	Mi57P (replaceable)	Mi58P (replaceable)
Environment	0 to 50°C; max RH 100%	-5 to 50°C; max RH 100%
Battery Type	4 x 1.5V; IEC LR44, A76	4 x 1.5V; IEC LR44, A76
Battery Life	approx. 300 hours of use	approx. 250 hours of use
Auto-off	after 8 minutes of non-use	after 8 minutes of non-use
Packaging dimensions	254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight	140 g	200 g

Replaceable combination pH/ORP electrode for pH58

Replace the electrode in a fast and simple way yourself! Just unscrew the plastic ring on the top of the electrode and replace the electrode with a new one.



Calibration, Maintenance & Cleaning Solutions

Choose from our wide selection of calibration, maintenance and cleaning solutions at page 59.



Accessories

- Mi57P** Replaceable electrode for ORP57
- Mi58P** Replaceable electrode for pH58
- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)



- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle
- MA9010** pH 10.01 buffer solution, 230 mL bottle
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL
- MA9020** ORP test solution (200/275 mV), 230 mL bottle
- MA753** Hard carrying case for 2 testers

Ordering Information

ORP57 PRO is supplied in a carton box complete with protective cap, batteries and instructions.

pH58 MAX is supplied in a carton box complete with protective cap, 20 mL pH 4.01 and pH 7.01 sachets of calibration solution, batteries and instructions.

pH51/pH54

Pocket-size Waterproof pH Meters

with replaceable electrode and manual calibration

Waterproof budget pH testers. Their waterproof casing and double junction replaceable electrodes make them suitable also for heavy duty applications, such as wastewater treatment and agriculture.

The modular design allows easy electrode and battery replacement. Manual calibration prolongs the battery life up to 1500 hours.

Specifications	pH51	pH54
Range	0.0 to 14.0 pH	0.00 to 14.00 pH
Resolution	0.1 pH	0.01 pH
Accuracy (@25°C)	±0.1 pH	±0.1 pH
Typical EMC Deviation	±0.1 pH	±0.1 pH
Calibration	manual at 2 points through trimmers	manual at 2 points through trimmers
pH electrode	MA73600 (replaceable)	MA73600 (replaceable)
Environment	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%
Battery Type	3 x 1.5V alkaline	3 x 1.5V alkaline
Battery Life	more than 1500 hours of continuous use	more than 1500 hours of continuous use
Packaging dimensions	254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight	186 g	186 g

Accessories

MA73600 Replaceable electrode for pH51 and pH54

M10000B Electrode rinse solution, 20 mL sachet (25 pcs)

M10004B pH 4.01 buffer solution 20 mL sachet (25 pcs)

M10007B pH 7.01 buffer solution 20 mL sachet (25 pcs)

M10010B pH 10.01 buffer solution 20 mL sachet (25 pcs)

MA9015 Electrode storage solution, 230 mL
MA753 Hard carrying case for 2 testers

Ordering Information

All testers are supplied in a carton box complete with calibration solution, batteries, instruction manual and screwdriver for calibration.

Packaging Information

Optionally pH51 is also available in a kit (**Mi5165**, **Mi5166**, **Mi5175**, **Mi5176**) together with **C65**, **C66**, **T75** or **T76**.



Ordering Information

pH600 is supplied in a plastic hard carrying case, complete with protective cap, calibration screwdriver, batteries and instructions.

pH600

pH Economical Pocket Tester

Milwaukee's budget pH tester with 1 point calibration is an easy-to-use instrument for applications such as aquarium, swimming pool and hydroponics.

Specifications	pH600
Range	0.0 to 14.0 pH
Resolution	0.1 pH
Accuracy	±0.1 pH
Calibration	manual, 1 point
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type / Battery Life	3 x 1.5V alkaline / 700 hours of use
Packaging dimensions	180 x 65 x 32 mm
Packaging weight	120 g



Accessories

M10004B pH 4.01 buffer solution 20 mL sachet (25 pcs)

M10007B pH 7.01 buffer solution 20 mL sachet (25 pcs)

M10010B pH 10.01 buffer solution, 20 mL sachet (25 pcs)

MA9015 Electrode storage solution, 230 mL

MA9016 Electrode cleaning solution, 230 mL



MC110 PRO/MC120 PRO pH Monitors

PRO pH monitor allows you to continuously monitor pH values directly in your reservoir. Features include: user selectable set point, visual LED alarm when values go above or below the set point and manual calibration. Each monitor is powered by a 12 VDC adapter and is ideal for applications such as Hydroponics and Aquarium.

The pH monitors are very simple to operate:

1. Hang your monitor above the reservoir;
2. Connect the adapter to the meter and plug in the power supply (make sure that your power supply is in a safe area away from the water);
3. Immerse 2/3 of the electrode in the solution;
4. The probe can now remain there permanently.

The monitors are supplied complete with a MA911B/2 pH electrode. Each monitor comes complete with a 12 VDC adapter and calibration solution.

Specifications	MC110 PRO	MC120 PRO
Range	0.0 to 14.0 pH	0.0 to 14.0 pH
Resolution	0.1 pH	0.1 pH
Accuracy (@25°C)	±0.2 pH	±0.2 pH
Calibration	manual, 2 points through trimmers on the meter front panel	manual, 2 points through trimmers on the meter front panel
Set point	3.5 to 7.5 pH	5.5 to 9.5 pH
Alarm	active when measurement is higher or lower than selected set point	active when measurement is higher or lower than selected set point
pH Electrode	MA911B/2 (included)	MA911B/2 (included)
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Power supply	12 VDC power adapter (included)	12 VDC adapter
Packaging dimensions	268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight	820 g	820 g

Accessories



- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution, 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution, 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution, 20 mL sachet (25 pcs)
- M10016B** Electrode cleaning solution, 20 mL sachet (25 pcs)
- MA9015** Electrode storage solution, 20 mL sachet (25 pcs)
- MA9016** Electrode cleaning solution, 20 mL sachet (25 pcs)
- MA9310** 12 VDC Adapter, 220 V
- MA9311** 12 VDC Adapter, 110 V
- MA911B/2** Double junction, gel filled pH electrode with 2 m cable



User selectable Hi/Low Set Point

A visual LED alarms when value goes above or below the set point the user selected.



Ordering Information

MC110 PRO is supplied complete with MA9310 12VDC adapter, MA911B/2 pH electrode, 20 mL pH 7.01 sachet of calibration solution, calibration screwdriver and instructions, in a carton box.

MC120 PRO is supplied complete with MA9310 12VDC adapter, MA911B/2 pH electrode, 20 mL pH 7.01 sachet of calibration solution, calibration screwdriver and instructions, in a carton box.

MC122 PRO/MC510 PRO/MC125 PRO pH & ORP Controllers

With Milwaukee's PRO Controllers you can monitor and control pH and/or ORP levels.

The Milwaukee Instruments PRO Controllers have a user selectable set point and a visual "Power Activated" LED notification light. Power to the controller box is turned on when the reading is Above or Below the selected set point. These MC Controllers are ideal for CO₂ or ozone dosing. This could be controlled by a solenoid valve (MA955).

With each Milwaukee PRO controller, your aquarium will have the individual attention that it needs.

Each unit comes with 12 VDC adapter, mounting kit, probe and starter calibration solution for pH (factory calibrated for ORP).

Professional pH controller especially designed for use in aquariums and hydroponic systems.



MA955 Solenoid valve for CO₂ dosing

Key features include:

- User selectable Hi/Low Set Point
- Manual 2 points calibration
- Visual LED alarm
- Supplied with 12 VDC adapter and mounting kit
- Power plug for CO₂ dosing
- Double junction pH electrode and/or platinum ORP electrode (BNC connector)

Specifications	MC122 PRO	MC510 PRO	MC125 PRO
Range	0.0 to 14.0 pH	±1000 mV (ORP)	0.00 to 14.00 pH; ±1000 mV (ORP)
Resolution	0.1 pH	1 mV (ORP)	0.1 pH; 1 mV (ORP)
Accuracy (@25°C)	±0.2 pH	±5 mV (ORP)	±0.2 pH; ±5 mV (ORP)
Set point pH	5.5 to 9.5 pH		4 to 8 pH
Set point ORP		0 to 600 mV	-200 to 600 mV
Alarm	active when measurement is higher or lower than selected set point	active when measurement is higher or lower than selected set point	active when measurement is higher or lower than selected set points
Output power socket	relay, 230V / 117V; 8A	relay, 230V / 117V; 8A	relay, 230V / 117V; 8A
Output	active when measurement is higher or lower than selected set point	active when measurement is higher or lower than selected set point	active when measurement is higher or lower than selected set points
pH Electrode	MA911B/2 (included)	MA921B/2 (included)	MA911B/2 (included)
ORP Electrode		MA921B/2 (included)	MA921B/2 (included)
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Power Supply	12 VDC power adapter (included)	12 VDC power adapter (included)	12 VDC power adapter (included)
Power Drivers	115VAC, 2A, 60Hz or 230VAC, 1A, 50Hz	115VAC, 2A, 60Hz or 230VAC, 1A, 50Hz	115VAC, 2A, 60Hz or 230VAC, 1A, 50Hz
Packaging dimensions	276 x 129 x 138 mm	276 x 129 x 138 mm	276 x 129 x 138 mm
Packaging weight	1.1 kg	0.9 kg	1.4 kg

Accessories



- M10000B** Electrode rinse solution 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)
- MA9015** Electrode storage solution 20 mL sachet (25 pcs)
- MA9310** 12 VDC Adapter, 220 V
- MA9311** 12 VDC Adapter, 110 V
- MA955** Solenoid valve with 1.5 m cable
- MA911B/2** Double junction, gel filled pH electrode with 1 m cable
- MA921B/2** ORP Electrode with BNC connector and 2 m cable

Ordering Information

MC122 PRO is supplied complete with MA9310 12 VDC adapter, MA911B/2 pH electrode, 20 mL pH4.01 sachet of calibration solution, 20 mL pH7.01 sachet of calibration solution, calibration screwdriver and instructions, in a carton box.

MC510 PRO is supplied complete with MA9310 12 VDC adapter, MA921B/2 ORP electrode and instructions, in a carton box.

MC125 PRO is supplied complete with MA9310 12 VDC adapter, power plug socket for ozone dosing, MA911B/2 pH electrode, MA921B/2 ORP electrode, 20 mL pH7.01 sachet of calibration solution, calibration screwdriver and instructions, in a carton box.



Control the pH of your tank/reservoir AUTOMATICALLY!



The **MC122 PRO** pH controller and dosing pump (**MP810/MP815**) provides fully automated pH control of aqueous solutions in hydroponic systems. It has been specifically designed to control the pH in mixing tanks for fertirrigation. The small and precise flow of the peristaltic pump allows you to maintain ideal pH values in your tank.

After selecting the desired pH setting from 5.5 to 9.5 pH, the pH controller measures the pH value of the solution and automatically adds pH adjustment (acid or alkaline) to change the liquid's pH to the selected level.

The **MP815** pump is with adjustable flow rate and dosing can be reduced by using a timer to turn the pump on and off at regular intervals.

Specifications	MP810	MP810 US
Max. Flow	1.5 L/h	0.6 L/h
Max. Pressure	2 bar	1.5 bar
Squeeze tubing	Santoprene	Santoprene
Ext. Tube connection	6 mm	6 mm
Power supply	240 VAC, 50-60 Hz	110 VAC, 60 Hz
Power consumption	7.7 W	0.42 W
Packaging dimensions	138 x 165 x 123 mm	138 x 165 x 123 mm
Packaging weight	820 g	620 g

Specifications	MP815	MP815 US
Adjustable Flow	0.0 to 2.2 L/h	0.0 to 2.2 L/h
Max. Pressure	2 bar	1.5 bar
Squeeze tubing	Santoprene	Santoprene
Ext. Tube connection	6 mm	6 mm
Power supply	240 VAC, 50-60 Hz	110 VAC, 60 Hz
Power consumption	7.7 W	0.42 W
Packaging dimensions	138 x 165 x 123 mm	138 x 165 x 123 mm
Packaging weight	820 g	620 g



MC122 PRO pH Controller

Ordering Information

MP810 and **MP815** are supplied complete with mounting bracket, screws, 1.5 meter Ext. PE tubing, Filter, Fitting, 2,6 meter Power cable.

MC122 PRO is supplied complete with MA9310 12 VDC adapter, MA911B/2 pH electrode, 20 mL pH4.01 sachet of calibration solution, 20 mL pH7.01 sachet of calibration solution, calibration screwdriver and instructions.

You can also order **MC122 PRO** with **MP810** in a kit (**MC720**).

Accessories

- M10000B** Electrode rinse solution 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)



- MA9015** Electrode storage solution 20 mL sachet (25 pcs)
- MA9310** 12 VDC Adapter, 220 V
- MA9311** 12 VDC Adapter, 110 V
- MA911B/2** Double junction, gel filled pH electrode with 1 m cable



MC720 kit, including MC122 pH Controller and MP810 Dosing Pump

MW170 MAX

Autoranging EC/TDS/NaCl/Temperature Laboratory Bench Meter

MW170 MAX is a compact and versatile bench meter that can measure up to four different parameters: EC, TDS, salinity (in PSU, g/L, percentage NaCl) and temperature. The main operating modes are setup, calibration, measurement and logging.

Features include:

- Easy to read LCD display
- Auto-off feature to prolong battery life
- All measurements can be temperature compensated automatically (ATC), or manually (MTC) with a user-selectable compensation coefficient. Temperature compensation can be disabled (NO TC) if the actual conductivity value is required.
- The auto-ranging feature for both EC and TDS measurements automatically sets the most suitable resolution for the tested sample.
- Available log space for up to 1000 records. Logged data can be exported using a USB cable
- Dedicated GLP key to store and recall data on system status
- Built-in rechargeable battery with 8 hours battery life



- Years warranty 3
- LOG
- USB
- ATC
- MTC
- Dual Display
- Self diagnostics
- GLP
- CE

Specifications	MW170 MAX
Range	EC 0.00 to 29.99 µS/cm; 30.0 to 299.9 µS/cm; 300 to 2999 µS/cm; 3.00 to 29.99 mS/cm; 30.0 to 200.0 mS/cm; up to 500.0 mS/cm absolute conductivity* TDS 0.00 to 14.99 mg/L (ppm); 15.0 to 149.9 mg/L (ppm); 150 to 1499 mg/L (ppm); 1.5 to 14.99 g/L (ppt); 15.0 to 100.0 g/L (ppt); up to 400.0 g/L absolute TDS* (with 0.80 factor) Salinity Temp 0.0 to 400.0 ‰ NaCl; 2.00 to 42.00 PSU; 0.00 to 80.00 g/L -20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	EC 0.01 µS/cm; 0.1 µS/cm; 1.0 µS/cm; 0.01 mS/cm; 0.1 mS/cm TDS 0.01 mg/L; 0.1 mg/L; 1.0 mg/L; 0.01 g/L; 0.1 g/L Salinity Temp 0.1% NaCl; 0.01 PSU; 0.01 g/L 0.1°C / 0.1°F
Accuracy (@ 25 °C / 77 °F)	EC ±1% of reading (±0.05 µS/cm or 1 digit, whichever is greater) TDS ±1% of reading (±0.03 ppm or 1 digit, whichever is greater) Salinity Temp ±1% of reading ±0.5 °C; ±0.9 °F
Calibration	EC/TDS Single cell factor calibration 6 standards: 84 µS/cm, 1413 µS/cm, 5.00 mS/cm, 12.88 mS/cm, 80.0 mS/cm, 111.8 mS/cm one-point offset: 0.00 µS/cm Salinity Temp one-point with MA9066 Salinity calibration solution 2 points, 0 to 50°C / 32 to 122°F
Temp. Compensation	ATC – automatic, from -5 to 100 °C (23 to 212 °F) MTC – manual, from -5 to 100 °C (23 to 212 °F) No TC – without temperature compensation
Temp. Coefficient	0.00 to 6.00 % / °C (EC & TDS only) Default value: 1.90 % / °C
Probe	MA814DB/1 4-ring probe with built-in temperature sensor (included)
TDS Factor	0.40 to 0.80 Default value: 0.50
Log	Maximum 1000 records; On demand, max. 200 samples; On stability, max. 200 samples Interval logging, max. 1000 samples (max. 100 lots)
PC connectivity	1 micro USB port
Environment	0 to 50 °C; max RH 95%
Power supply	12 VDC adapter (included)
Battery life	8 hours
Packaging dimensions	335 x 120 x 255 mm
Packaging weight	2.16 kg

(*) Absolute conductivity (or TDS) is the conductivity value without temperature compensation.

More accurate readings with the 4-RING MA814DB/1 EC/TDS/NaCl and Temperature probe!

Conductivity readings are performed by applying an alternate current to the 4-ring probe which creates a variable voltage depending on the conductivity.



Rear Connector Panel layout

Communication to the PC is done via a micro USB port.



Accessories

- | | |
|--|---|
| MA814DB/1 EC/Temperature probe with DIN connector and 1 m cable | MA9065 111.8 mS/cm calibration solution, 230 mL bottle |
| MA9060 12880 µS/cm calibration solution, 230 mL bottle | MA9066 100% NaCl calibration solution, 230 mL bottle |
| MA9061 1413 µS/cm calibration solution, 230 mL bottle | MA9069 5000 µS/cm solution, 230 mL bottle |
| MA9063 84 µS/cm calibration solution, 230 mL bottle | MA9310 12 VDC Adapter, 220 V |
| MA9064 80000 µS/cm conductivity solution, 230 mL bottle | MA9311 12 VDC Adapter, 110 V |
| | MA9315 Electrode holder |
| | MA9350 RS232 connection cable with 2 meters cable |

Ordering Information

- MW170 MAX is supplied complete with
- MA814DB/1 EC/TDS/NaCl/Temperature Probe
 - MA9315 Electrode Holder
 - MA9310 12 VDC Adapter
 - Instruction manual

MW306 MAX

Automatic & Logging EC/TDS/NaCl/Temperature Meter

MW306 MAX is a waterproof and portable meter with a user-friendly interface. Designed to measure four different parameters – EC, TDS, percentage of salinity in psu (NaCl%) and temperature – the meter is suitable for multiple applications.

- IP67 waterproof casing
- Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time
- Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots)
- auto-ranging feature for both EC and TDS measurements automatically sets the most suitable resolution for the tested sample.
- GLP data review and the data can be transferred to a PC through a USB port.

Hard Carrying Case

The meter is supplied in a hard carrying case ideal for field measurements.



- Years warranty 2
- LOG
- USB
- ATC
- MTC
- Self diagnostics
- CE
- IP67
- GLP



Specifications	MW306 MAX
Range	EC 0.00 to 29.99 µS/cm; 30.0 to 299.9 µS/cm; 300 to 2999 µS/cm; 3.00 to 29.99 mS/cm; 30.0 to 200.0 mS/cm; up to 500.0 mS/cm absolute EC* TDS 0.00 to 14.99 mg/L; 15.0 to 149.9 mg/L; 150 to 1499 mg/L; 1.50 to 14.99 g/L; 15.0 to 100.0 g/L; up to 400.0 g/L absolute (*) TDS (with 0.80 factor) Salinity 0.0 to 400.0 % NaCl 2.00 to 42.00 PSU Temp 0.00 to 80.00 g/L -20.0 to 120.0 °C; -4.0 to 248.0 °F
Resolution	EC 0.01 µS/cm; 0.1 µS/cm; 1 µS/cm; 0.01 mS/cm; 0.1 mS/cm TDS 0.01 mg/L; 0.1 mg/L; 1 mg/L; 0.01 g/L; 0.1 g/L Salinity 0.1% NaCl; 0.01 PSU; 0.01 g/L Temp 0.1 °C; 0.1 °F
Accuracy (@ 25 °C / 77 °F)	EC ±1% of reading (±0.05 µS/cm or 1 digit, whichever is greater) TDS ±1% of reading (±0.03 ppm or 1 digit, whichever is greater) Salinity ±1% of reading Temp ±0.5 °C; ±0.9 °F
Calibration	EC/TDS Single cell factor calibration 6 standards: 84 µS/cm, 1413 µS/cm, 5.00 mS/cm, 12.88 mS/cm, 80.0 mS/cm, 111.8 mS/cm one-point offset: 0.00 µS/cm one-point with MA9066 Salinity calibration solution Salinity
Temperature Compensation	ATC – automatic, from -5 to 100 °C (23 to 212 °F) MTC – manual, from -20 to 120 °C (23 to 212 °F) NO TC – without temperature compensation
Temperature Coefficient	0.00 to 6.00 % / °C (EC & TDS only) Default value: 1.90 % / °C
TDS Factor	0.40 to 0.80 Default value: 0.50
EC Probe	MA815D/1
Log	Max. 1000 log records (stored in up to 100 lots) On demand, 200 logs / On stability, 200 logs / Interval logging, 1000 logs
PC connectivity	1 micro USB port
Power supply	12 VDC adapter (included)
Battery life	Approx. 200 hours of use
Auto-off	5, 10, 30, 60 minutes or off
Environment	0 to 50 °C; max RH 95%
Casing	IP67
Packaging dimensions	305 x 280 x 115 mm
Packaging weight	1.22 kg

(*) Absolute conductivity (or TDS) is the conductivity value without temperature compensation.

Accessories



- MA815D/1** 4-ring EC/TDS/NaCl/Temperature probe with DIN connector and 1 meter cable
- M10030B** 12880 µS/cm calibration solution, 20 mL sachet, 25 pcs.
- M10031B** 1413 µS/cm calibration solution, 20 mL sachet, 25 pcs.
- M10035B** 111.8 mS/cm calibration solution, 20 mL sachet, 25 pcs.
- MA9060** 12880 µS/cm calibration solution, 230 mL bottle
- MA9061** 1413 µS/cm calibration solution, 230 mL bottle
- MA9063** 84 µS/cm calibration solution, 230 mL bottle
- MA9065** 111.8 mS/cm calibration solution, 230 mL bottle
- MA9066** 100% NaCl calibration solution, 230 mL bottle
- MA9069** 5000 µS/cm solution, 230 mL bottle

Ordering Information

MW306 MAX is supplied in a hard carrying case complete with

- MA815D/1 4-ring EC/TDS/NaCl/Temperature probe with DIN connector and 1 meter cable
- 12 VDC adapter
- Micro USB cable
- Instrument quality certificate
- Instruction manual

MW301 PRO/MW302 PRO/MW401 PRO/MW402 PRO

Budget Conductivity & TDS

Portable Meters for fast and reliable results

MW301 PRO, MW302 PRO, MW401 PRO and MW402 PRO are compact microprocessor-based Conductivity and TDS Portable Meters. These handy and ergonomically designed portable meters are ideal for anyone working on a low budget and still requires fast and reliable measurements.

These portable meters are suitable for a wide range of applications, such as Educational, Agriculture and Horticulture, as well as water and environmental analysis.

These portable meters with Automatic Temperature Compensation have a small and ergonomic case design. Other features include large and easy to read LCD and long battery life. Each meter is supplied complete with Conductivity/TDS probe with 1 meter cable and calibration solution.

Choose your portable EC & TDS meter according to the proper EC/TDS ranges for your application:

- **MW301 PRO:** 0 to 1999 $\mu\text{S}/\text{cm}$ with a 1 $\mu\text{S}/\text{cm}$ resolution;
- **MW302 PRO:** 0.0 to 10.0 mS/cm with a 0.1 mS/cm resolution;
- **MW401 PRO:** 0 to 1999 mg/L (ppm) with a 1 mg/L resolution;
- **MW402 PRO:** 0.0 to 10.0 g/L (ppt) with a 0.1 g/L resolution.



Specifications	MW301 PRO	MW302 PRO	MW401 PRO	MW402 PRO
Range	0 to 1999 $\mu\text{S}/\text{cm}$	0.0 to 10.0 mS/cm	0 to 1999 mg/L (ppm)	0.0 to 10.0 g/L (ppt)
Resolution	1 $\mu\text{S}/\text{cm}$	0.1 mS/cm	1 mg/L (ppm)	0.1 g/L (ppt)
Accuracy (@25°C)	$\pm 2\%$ Full Scale	± 2 Full Scale	$\pm 2\%$ Full Scale	± 2 Full Scale
Conversion factor			0.5	0.5
Calibration Solutions (included)	1413 $\mu\text{S}/\text{cm}$ (M10031B)	1413 $\mu\text{S}/\text{cm}$ (M10031B)	1382 mg/L (M10032B)	6.44 g/L (M10038B)
Conductivity probe	SE510 (included)	SE520 (included)	SE510 (included)	SE520 (included)
Temperature Compensation	automatic, from 5 to 50°C	automatic, from 5 to 50°C	automatic, from 5 to 50°C	automatic, from 5 to 50°C
Environment	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%
Battery Type	1 x 9V alkaline (included)	1 x 9V alkaline (included)	1 x 9V alkaline (included)	1 x 9V alkaline (included)
Battery Life	approx. 300 hours of use	approx. 300 hours of use	approx. 300 hours of use	approx. 300 hours of use
Packaging dimensions	212 x 145 x 67 mm	212 x 145 x 67 mm	212 x 145 x 67 mm	212 x 145 x 67 mm
Packaging weight	440 g	440 g	440 g	440 g

Accessories

- | | |
|--|---|
| SE510 EC/TDS probe with DIN connector and 1 m cable for MW301, MW401 | M10038B 6.44 ppt (g/l) calibration solution, 20 mL (25 pcs) |
| SE520 EC/TDS probe with DIN connector and 1 m cable for MW302, MW402 | MA9060 12880 $\mu\text{S}/\text{cm}$ calibration solution, 230 mL bottle |
| M10031B 1413 $\mu\text{S}/\text{cm}$ calibration solution, 20 mL (25 pcs) | MA9061 1413 $\mu\text{S}/\text{cm}$ calibration solution, 230 mL bottle |
| M10032B 1382 ppm (mg/L) calibration solution, 20 mL (25 pcs) | MA9062 1382 ppm TDS solution, 230 mL bottle |

Ordering Information

- MW301 PRO** is supplied complete with SE510 EC probe, 20 mL 1413 $\mu\text{S}/\text{cm}$ sachet of calibration solution, screwdriver for calibration, 9V battery and instructions.
- MW302 PRO** is supplied complete with SE520 EC probe, 20 mL 1413 $\mu\text{S}/\text{cm}$ sachet of calibration solution, screwdriver for calibration, 9V battery and instructions.
- MW401 PRO** is supplied complete with SE510 EC probe, 20 mL 1382 ppm sachet of calibration solution, screwdriver for calibration, 9V battery and instructions.
- MW402 PRO** is supplied complete with SE520 EC probe, 20 mL 6.44 ppt sachet of calibration solution, screwdriver for calibration, 9V battery and instructions.

Packaging Information

MW301 PRO, MW302 PRO, MW401 PRO, MW402 PRO are supplied in a carton color box. Optionally they can be ordered in a hard carrying case (Mi0028).



EC59 PRO/EC60 PRO

Pocket-size EC/TDS/Temp Meters



- Years warranty 2
- ATC
- IP65
- Dual Display
- Self diagnostics
- CE
- Electrode Replaceable



Water-resistant pocket-size EC/TDS/Temp meters include features such as replaceable probe, temperature in °C or °F, automatic temperature compensation with adjustable β, battery level indicator, stability indicator, automatic shut-off and automatic calibration all in a floating, water-resistant casing.

EC59 PRO shows on the dual-level LCD the EC (3999 µS/cm) or TDS (2000 ppm) value. It also displays the temperature from 0.0 to 60.0°C (or 32.0 to 140.0°F) on the secondary level at the same time.

EC60 PRO shows on the dual-level LCD the EC (20.00 mS/cm) or TDS (10.00 ppt) value. It also displays the temperature from 0.0 to 60.0°C (or 32.0 to 140.0°F) on the secondary level at the same time.

Specifications			
		EC59 PRO	EC60 PRO
Range	EC TDS Temp	3999 µS/cm 2000 ppm 0.0 to 60.0°C / 32.0 to 140.0°F	20.00 mS/cm 10.00 ppt 0.0 to 60.0°C // 32.0 to 140.0°F
Resolution	EC TDS Temp	1 µS/cm 1 ppm 0.1°C / 0.1°F	0.01 mS/cm 0.01 ppt 0.1°C / 0.1°F
Accuracy (@20°C)	EC TDS Temp	±2% Full Scale ±2% Full Scale ±0.5°C / ±1°F	±2% Full Scale ±2% Full Scale ±0.5°C / ±1°F
Typical EMC Deviation	EC TDS Temp	±2% Full Scale ±2% Full Scale ±0.5°C / ±1°F	±2% Full Scale ±2% Full Scale ±0.5°C / ±1°F
Calibration		automatic, 1 point with 1413 µS/cm calibration solution	automatic, 1 point with 12880 µS/cm calibration solution
Temperature Compensation		automatic, with β=0.0 to 2.4%/°C	automatic, with β=0.0 to 2.4%/°C
Probe		Mi59P (replaceable)	Mi59P (replaceable)
Environment		0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%
Battery Type		4 x 1.5V; IEC LR44, A76 (included)	4 x 1.5V; IEC LR44, A76 (included)
Battery Life		approx. 100 hours of use	approx. 100 hours of use
Auto-off		after 8 minutes of non-use	after 8 minutes of non-use
Packaging dimensions		254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight		180 g	180 g

Accessories

- Mi59P** Replaceable probe for EC59 & EC60
- M10000B** Rinse solution, 20 mL sachet, 25 pcs
- M10030B** 12880 µS/cm calibration solution, 20 mL sachet, 25 pcs
- M10031B** 1413 µS/cm calibration solution, 20 mL sachet, 25 pcs
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL sachet, (25 pcs)

- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL sachet, (25 pcs)
- MA9060** 12880 µS/cm calibration solution, 230 mL bottle
- MA9061** 1413 µS/cm calibration solution, 230 mL bottle
- MA9016** Cleaning solution, 230 mL bottle
- MA753** Hard carrying case for 2 testers



EC/TDS/Temp probe

Exposed temperature sensor

Replaceable EC/TDS probe

Replaceable probe

Replace the probe in a fast and simple way yourself! Just unscrew the plastic ring on the top of the probe and replace the probe with a new one.



Ordering Information

EC59 PRO is supplied in a carton box complete with protective cap, 20 mL 1413 µS/cm sachet of calibration solution, batteries and instructions.

EC60 PRO is supplied in a carton box complete with protective cap, 20 mL 12880 µS/cm sachet of calibration solution, batteries and instructions.

Optionally **EC59 PRO** and **EC60 PRO** is also available in a kit (**Mi5559** or **Mi5560**) together with **PH55 PRO** pH/Temp Meter.



C65/C66/T75/T76

Pocket-size Waterproof Conductivity & TDS testers with replaceable probe and manual calibration

Waterproof testers designed for all applications. Their waterproof casing and replaceable probe make them suitable also for heavy duty applications, such as wastewater treatment and agriculture. The modular design allows easy probe and battery replacement.

Specifications	C65	C66	T75	T76
Range	0 to 1999 µS/cm	0.00 to 10.00 mS/cm	0 to 1999 ppm (mg/L)	0 to 9990 ppm (mg/L)
Resolution	1 µS/cm	0.01 mS/cm	1 ppm (mg/L)	10 ppm (mg/L)
Accuracy	±2% Full Scale	±2% Full Scale	±2% Full Scale	±2% Full Scale
Typical EMC Deviation	±2% Full Scale	±2% Full Scale	±2% Full Scale	±2% Full Scale
Temp. Compensation	automatic, with β=2%/°C	automatic, with β=2%/°C	automatic, with β=2%/°C	automatic, with β=2%/°C
TDS Factor			0.5	0.5
Calibration	manual at 1 point	manual at 1 point	manual at 1 point	manual at 1 point
Probe	MA73075 (replaceable)	MA73076 (replaceable)	MA73075 (replaceable)	MA73076 (replaceable)
Environment	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%
Battery Type	3 x 1.5V alkaline	3 x 1.5V alkaline	3 x 1.5V alkaline	3 x 1.5V alkaline
Battery Life	approx. 250 hours of use	approx. 250 hours of use	approx. 250 hours of use	approx. 250 hours of use
Packaging dimensions	254 x 67 x 47 mm	254 x 67 x 47 mm	254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight	157 g	156 g	157 g	156 g



Accessories

- MA73075** Replaceable conductivity probe, LR
- MA73076** Replaceable conductivity probe, HR
- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10030B** 12880 µS/cm calibration solution, 20 mL sachet, 25 pcs
- M10031B** 1413 µS/cm calibration solution, 20 mL sachet, 25 pcs

- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL sachet, (25 pcs)
- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL sachet, (25 pcs)
- M10080B** 800 ppm calibration solution, 20 mL sachet (25 pcs)
- MA753** Hard carrying case for 2 testers



Ordering Information

All testers are supplied in a carton box complete with calibration solution, batteries, instruction manual and screwdriver for calibration.

Optionally **C65**, **C66**, **T75** and **T76** is also available in a kit (**Mi5165**, **Mi5166**, **Mi5175**, **Mi5176**) together with **pH51** pH Meter.

CD600/CD601/CD610/CD611/CD97

EC & TDS Economical Pocket Testers

Milwaukee's economical testers are easy-to-use and low cost instruments to measure quick and reliable EC or TDS values. Milwaukee provides you with a range of pocket testers that will allow you to measure from very low to very high conductivity solutions. All EC/TDS testers compensate for the temperature variance automatically.

Specifications	CD600	CD601	CD610	CD611	CD97
Range	0 to 1990 ppm	0 to 1990 µS/cm	0 to 10000 ppm	0 to 20000 µS/cm	0 to 1000 ppm
Resolution	10 ppm	10 µS/cm	100 ppm	100 µS/cm	1 ppm
Accuracy	±2% Full scale	±2% Full scale	±2% Full scale	±2% Full scale	±10 ppm
Calibration	manual, 1 point	manual, 1 point	manual, 1 point	manual, 1 point	manual, 1 point
Temp. Comp.	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C
Environment	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%
Battery Type	4 x 1.5V alkaline	4 x 1.5V alkaline	4 x 1.5V alkaline	4 x 1.5V alkaline	4 x 1.5V alkaline
Battery Life	350 hours of use	350 hours of use	350 hours of use	350 hours of use	350 hours of use
Packaging dim.	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm
Packaging weight	120 g	120 g	120 g	120 g	120 g

Accessories

- M10030B** 12880 µS/cm calibration solution, 20 mL (25 pcs)
- M10031B** 1413 µS/cm calibration solution, 20 mL (25 pcs)
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL (25 pcs)

- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL (25 pcs)
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL



Ordering Information

CD600, **CD601**, **CD610**, **CD611** and **CD97** are supplied in a plastic hard carrying case, complete with protective cap, calibration screwdriver, batteries and instructions.

MC310 PRO/MC410 PRO Conductivity/TDS Monitors



Reliable Conductivity and TDS monitors with Automatic temperature compensation and 1 point manual calibration powered by a 12 VDC adapter. They are ideal for the hydroponic market and allow you to continuously monitor EC or TDS values directly in your reservoir.

Other features include: user selectable set point, visual LED alarm when values go above/below (selectable by the user) the set point.

The monitors are very simple to operate:

1. Hang your monitor above your reservoir
2. Connect the adapter to the meter and plug in the power supply (make sure that your power supply is in a safe area from the water!)
3. Immerse 2/3 of the probe in the solution
4. The probe can now remain there permanently.

User selectable Hi/Low Set Point

A visual LED alarms when value goes above or below the set point the user selected.



Specifications

	MC310 PRO	MC410 PRO
Range	0.0 to 10.0 mS/cm	0 to 1990 ppm
Resolution	0.1 mS/cm	10 ppm
Accuracy (@25°C)	±2% Full Scale	±2% Full Scale
Conversion factor		0.7
Set point	1 to 5 mS/cm	100 to 1900 ppm
Alarm	active when the measurement is higher or lower than the set point	active when the measurement is higher or lower than the set point
Temperature compensation	automatic, from 5 to 50°C	automatic, from 5 to 50°C
Environment	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%
Probe	MA812/2 (included)	MA812/2 (included)
Power supply	12 VDC power adapter (included)	12 VDC power adapter (included)
Packaging dimensions	268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight	820 g	820 g

Accessories

- M10000B Electrode rinse solution, 20 mL sachet (25 pcs)
- M10031B 1413 µS/cm calibration solution, 20 mL sachet (25 pcs)
- M10032B 1382 ppm calibration solution, 20 mL sachet (25 pcs)
- MA9061 1413 µS/cm calibration solution, 230 mL bottle
- MA9062 1382 ppm TDS solution, 230 mL bottle
- MA9310 12 VDC Adapter, 220 V
- MA9311 12 VDC Adapter, 110 V
- MA812/2 Conductivity probe with 2 m cable



Ordering Information

MC310 PRO is supplied complete with MA9310 12VDC adapter, MA812/2 EC probe, 20 mL 5.00 mS/cm sachet of calibration solution, screwdriver for calibration and instruction, in a carton box.

MC410 PRO is supplied complete with MA9310 12VDC adapter, MA812/2 TDS probe, 20 mL 1500 ppm sachet of calibration solution, screwdriver for calibration and instruction, in a carton box.



MC311 PRO

Conductivity Controller

MC740 & MC745 control the EC & nutrient dosage in your tank AUTOMATICALLY!

The **MC311 PRO** EC controller and dosing pump (**MP810**) provides fully automated EC control of aqueous solutions in hydroponic systems.


The **MC740** kit contains the **MC311 PRO** controller with one **MP810** dosing pump, the **MC745** kit contains the **MC311 PRO** controller with two **MP810** dosing pumps!

Accessories:

MA812/2 EC probe with 2 meter cable



Years warranty
2
ALARM
CE



Specifications	MC311 PRO
Range	0.0 to 10.0 mS/cm
Resolution	0.1 mS/cm
Accuracy (@25°C)	±2% Full scale
Set point	0.8 to 2.8 mS/cm
Alarm	active when measurement is higher or lower than the selected set point
Temp. compensation	automatic
Output	active when measurement is higher or lower than the selected set point
Power supply	12 VDC adapter
Packaging dimensions	278 x 132 x 138 mm
Packaging weight	1.1 kg

EC40 EC Waterproof Nutrient Stick

- Readings are displayed with 20 LEDs graph bar
- Range 0.2 to 4 mS/cm
- The alarm feature is user settable and is displayed on the LED bar
- No calibration required
- Auto-ON/OFF function
- The auto-check feature indicates the battery level
- Waterproof and floating design makes the stick an appropriate tool for stirring nutrient solutions in a bucket/tank

Specifications	EC40
Range	0.2 to 4 mS/cm 2 to 40 CF 140 to 2800 ppm (0.7) 100 to 2000 ppm (0.5)
Resolution	0.1 mS/cm 1 CF 70 ppm 50 ppm
Accuracy	± 4% of reading ± 1 resolution point
Probe	Graphite probe in ABC+PC body
Temp. compensation	automatic
Battery Type	3 x 1.5V AA alkaline
Battery Life	approx. 3 years
Packaging dimensions	444 x dia 56 mm
Packaging weight	415 g



Graphite EC probe with ATC



MW190 MAX Dissolved Oxygen/Temperature Bench Meter

- Years warranty 3
- LOG
- USB
- ATC
- GLP
- Points 2
- Dual Display
- Self diagnostics
- CE



MW190 MAX is a compact and versatile bench meter designed for testing dissolved oxygen in the pharmaceutical and food industry, as well as monitoring in water treatment plants. Concentration measurements are automatically compensated for temperature and salinity. Salinity and altitude can be configured in Setup. Temperature is automatically measured (in both degree Celsius and Fahrenheit) and compensated.

Other features include:

- Easy to read LCD display
- Built-in rechargeable battery with an 8-hour capacity
- Auto-off feature to prolong battery life
- Battery charger with battery monitor
- Internal clock and date to keep track of different time-dependent functions (calibration timestamp, calibration time out)
- Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time
- Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots)
- Logged data can be exported using a USB cable or directly on a USB flash drive
- Dedicated GLP key to store and recall data on system status

For accurate measurements, use the electrode holder supplied with the bench meter.

Specifications	MW190 MAX
Range	O ₂ 0.00 to 45.00 mg/L (ppm) % Saturation O ₂ 0.0 to 300.0% Temp -20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	O ₂ 0.01 mg/L (ppm) % Saturation O ₂ 0.1% Temp 0.1°C (0.1°F)
Accuracy	O ₂ ±1.5% of reading ±1 digit % Saturation O ₂ ±1.5% of reading ±1 digit Temp ±0.4°C (±0.8°F)
Calibration	One or two points 0% (MA9070) and 100% (water saturated air)
Temperature Compensation	automatic, from 0.0 to 50.0°C / 32.0 to 122.0°F
Altitude Compensation	-500 to 4000 m (with 100 m resolution)
Salinity Compensation	0 to 40 g/L (with 1 g/L resolution)
Probe	MA845 (included)
Logging memory	Max. 1000 log records (stored in up to 100 lots) On demand, 200 logs, On stability, 200 logs Interval logging, 1000 logs
PC connectivity	1 USB type A port, 1 micro USB port
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Power supply	12 VDC adapter (included)
Battery Life	8 hours
Packaging dimensions	335 x 120 x 255 mm
Packaging weight	2.2 kg

Ordering Information



MW190 MAX is supplied complete with:

- MA845 DO/Temp Polarographic probe
- MA841 Spare membrane (2 pcs)
- MA9071 Electrolyte solution
- MA9315 Electrode holder
- 12 VDC Adapter
- USB cable
- Instruction manual

Accessories

- | | | |
|---|--|--|
| <p>MA9070 Zero Oxygen Solution, 230 mL bottle</p> <p>MA9071 Refilling Electrolyte Solution, 230 mL bottle</p> <p>MA9310 12 VDC Adapter, 220 V</p> <p>MA9311 12 VDC Adapter, 110 V</p> | <p>MA841 Spare membrane (5 pcs)</p> <p>MA845 DO/Temp probe</p> <p>MA9315 Electrode holder</p> | |
|---|--|--|

MW605 MAX Dissolved Oxygen/Temperature Portable Meter

MW605 MAX is a portable, IP67 rated meter designed for fresh and saltwater measurements of dissolved oxygen (DO). The MW605 meter is compatible with MA860 galvanic DO probe. Galvanic probes require no conditioning and thus the instrument is ready to measure when it is powered on.

Concentration measurements are automatically compensated for temperature and salinity. Temperature is automatically measured (in both degree Celsius and Fahrenheit) and compensated. Salinity and altitude can be configured in Setup.

Other features include:

- IP67 waterproof casing
- Auto-off feature to prolong battery life
- One or two % saturation calibration points at 100% (water saturated air) and 0% (zero oxygen solution)
- Dedicated GLP key to store and recall data on system status
- Available log space for up to 1000 records
- Logged data can be exported using a USB cable



Specifications	MW605 MAX
Range	O ₂ 0.00 to 45.00 mg/L (ppm) % Saturation O ₂ 0.0 to 300% Temp -20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	O ₂ 0.01 mg/L (ppm) % Saturation O ₂ 0.1% Temp 0.1°C (0.1°F)
Accuracy	O ₂ ±1.5% of reading ±1 digit % Saturation O ₂ ±1.5% of reading ±1 digit Temp ±0.4°C (±0.8°F)
Calibration	One or two % saturation calibration points 0% (MA9070) and 100% (water saturated air)
Temperature Compensation	automatic, from 0.0 to 50.0°C / 32.0 to 122.0°F
Altitude Compensation	-500 to 4000 m (with 100 m resolution)
Salinity Compensation	Manual, from 0 to 40 g/L (with 1 g/L resolution)
Probe	MA860 (included)
Logging memory	Max. 1000 log records (stored in up to 100 lots) On demand, 200 logs, On stability, 200 logs Interval logging, 1000 logs
PC connectivity	1 micro USB port
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type	3 x 1.5V alkaline AA (included)
Battery Life	approx. 200 hours of use
Auto-off	after 4 hours of non-use
Packaging dimensions	305 x 280 x 115 mm
Packaging weight	1.4 kg

Accessories

- MA9072S** Refilling Electrolyte solution, 30 mL bottle
- MA860** D.O. Probe
- MA861** Spare membrane (5 pcs)



Ordering Information

MW605 MAX portable meter is delivered in a rugged carrying case and is supplied with: MA860 Dissolved Oxygen and Temperature galvanic probe, MA861 Dissolved Oxygen membrane with o-ring (2 pcs.), MA9072S Oxygen electrolyte solution, Probe protective cap, 1.5V alkaline AA battery (3 pcs.), Micro USB cable, Instrument quality certificate and Instruction manual.

Hard Carrying Case

MW605 MAX is supplied complete in a hard carrying case complete with a D.O. probe, spare membranes, calibration solution, battery, micro USB cable and instructions.






MW600 PRO

Budget Dissolved Oxygen Portable Meter for fast and reliable results

The **MW600 PRO** is a compact microprocessor-based Portable Dissolved Oxygen meter. This handy and ergonomically designed portable meter is ideal for anyone working on a low budget and still requires fast and reliable measurements. This portable meter measures Dissolved Oxygen with a Polarographic probe and is suitable for a wide range of applications, such as Educational and Aquaculture, as well as water and environmental analysis.

Other features include small and ergonomic case design, large and easy to read LCD, low battery warning, easy to replace screw on cap membranes and long battery life.

MW600 PRO is supplied complete with a MA840 D.O. polarographic probe with 4 meter cable, calibration screwdriver, 2 spare membranes, MA9071 (30 mL) electrolyte solution, battery and instructions.



The **MW600 PRO** calibrates easily in 2 points (at 100% saturated air and in 0 Oxygen solution) and has Automatic Temperature Compensation which guarantees the highest accuracy.

Specifications	MW600 PRO
Range	O ₂ 0.0 to 19.9 mg/L
Resolution	O ₂ 0.1 mg/L
Accuracy (@25°C)	O ₂ ±1.5% Full Scale
Calibration	manual on 2 points (zero and slope)
Temperature Compensation	automatic from 0 to 30°C
Probe	MA840 (included)
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type	9V alkaline (included)
Battery Life	approximately 70 hours of use
Packaging dimensions	268 x 122 x 118 mm
Packaging weight	880 g

ALTITUDE & SALINITY COMPENSATION:

If the sample contains salts or if you are performing the measurements at altitude different from sea level, the readout values must be corrected, taking into account the lower degree of oxygen solubility.

Altitude Compensation: all the readouts are referred to sea level, thus the displayed measurements are higher than the actual values. In fact, altitude affects D.O. concentration by decreasing its value.

The table on the left reports the oxygen solubility at various temperatures and altitudes, based on sea level barometric pressure of 760 mmHg.

This gives an idea of the error that can be introduced at different altitudes and allows to calculate the quantity to be subtracted to correct the reading.

Large and easy-to-read display

MW600 PRO offers highly stable and accurate readings with large LCD display.



Altitude, Meters above Sea Level									
°C	0 m	300 m	600 m	900 m	1200 m	1500 m	1800 m	°F	
0	14.6	14.1	13.6	13.2	12.7	12.3	11.8	11.8	32.0
2	13.8	13.3	12.9	12.4	12.0	11.6	11.2	11.2	35.6
4	13.1	12.7	12.2	11.9	11.4	11.0	10.6	10.6	39.2
6	12.4	12.0	11.6	11.2	10.8	10.4	10.1	10.1	42.8
8	11.8	11.4	11.0	10.6	10.3	9.9	9.6	9.6	46.4
10	11.3	10.9	10.5	10.2	9.8	9.5	9.2	9.2	50.0
12	10.8	10.4	10.1	9.7	9.4	9.1	8.8	8.8	53.6
14	10.3	9.9	9.6	9.3	9.0	8.7	8.3	8.3	57.2
16	9.9	9.7	9.2	8.9	8.6	8.3	8.0	8.0	60.8
18	9.5	9.2	8.7	8.6	8.3	8.0	7.7	7.7	64.4
20	9.1	8.8	8.5	8.2	7.9	7.7	7.4	7.4	68.0
22	8.7	8.4	8.1	7.8	7.7	7.3	7.1	7.1	71.6
24	8.4	8.1	7.8	7.5	7.3	7.1	6.8	6.8	75.2
26	8.1	7.8	7.5	7.3	7.0	6.8	6.6	6.6	78.8
28	7.8	7.5	7.3	7.0	6.8	6.6	6.3	6.3	82.4
30	7.5	7.2	7.0	6.8	6.5	6.3	6.1	6.1	86.0
32	7.3	7.1	6.8	6.6	6.4	6.1	5.9	5.9	89.6
34	7.1	6.9	6.6	6.4	6.2	6.0	5.8	5.8	93.2
36	6.8	6.6	6.3	6.1	5.9	5.7	5.5	5.5	96.8
38	6.6	6.4	6.2	5.9	5.7	5.6	5.4	5.4	100.4
40	6.4	6.2	6.0	5.8	5.6	5.4	5.2	5.2	104.0

Accessories

- MA9070** Zero Oxygen calibration solution, 230 mL bottle
- MA9071** Refilling Electrolyte solution, 230 mL bottle



- MA840** D.O. Probe
- MA841** Spare membrane (5 pcs)
- MA751** Hard carrying case

Ordering Information

MW600 PRO is supplied complete with MA840 probe, 2 spare membranes, 20 mL bottle of electrolyte solution, calibration screwdriver, 9V battery and instructions.



MW801 PRO/MW802 PRO

Budget pH/EC/TDS Combined Portable Meters for fast and reliable results

MW801 PRO and MW802 PRO are compact microprocessor-based Portable Meters. These meters allow you to measure pH, EC (conductivity) and TDS with just one instrument and one single probe!

These easy and fast to calibrate portable meters have a small and ergonomic case design. Other features include large and easy to read LCD and long battery life.

Both meters calibrate manually in pH, Conductivity and TDS.

Each meter is supplied with the MA850 interchangeable probe with 1 meter cable to measure pH, Conductivity and TDS. The pH electrode utilizes a fiber junction to reduce contamination when measuring fertilizer solutions.

- The **MW801 PRO** with a Conductivity range that goes up to 1990 $\mu\text{S/cm}$ and TDS range that goes up to 1990 ppm is an ideal tool for drinking water measurements.
- The **MW802 PRO**, with a conductivity range that goes up to 6.00 mS/cm and the TDS up to 4000 ppm is ideal for testing in crop production.



- Years warranty 2
- ATC
- Points 2
- Dual Display
- MULTI
- Self diagnostics

Specifications	MW801 PRO	MW802 PRO
Range	pH 0.0 to 14.0 pH EC 0 to 1990 $\mu\text{S/cm}$ TDS 0 to 1990 ppm	0.00 to 14.00 pH 0.00 to 6.00 mS/cm 0 to 4000 ppm
Resolution	pH 0.1 pH EC 10 $\mu\text{S/cm}$ TDS 10 ppm	0.10 pH 0.10 mS/cm 10 ppm
Accuracy (@25°C)	pH ± 0.2 pH EC/TDS $\pm 2\%$ Full Scale	± 0.20 pH $\pm 2\%$ Full Scale
Calibration Solutions	M10007 (pH 7.01) M10031 (1413 $\mu\text{S/cm}$) M10032 (1382 ppm)	M10007 (pH 7.01) M10031 (1413 $\mu\text{S/cm}$)
Conversion Factor	0.5	0.68
Calibration	manual, at 1 point	manual, at 1 point
Temperature Compensation	automatic, from 0 to 50°C	automatic, from 0 to 50°C
Probe	SE600 combination pH/EC/TDS/probe (included)	SE600 combination pH/EC/TDS/probe (included)
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type	1 x 9V alkaline	1 x 9V alkaline
Battery Life	150 hours of use	150 hours of use
Packaging dimensions	268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight	640 g	720 g

Large and easy-to-read display

MW801 PRO and MW802 PRO offer highly stable and accurate readings with large LCD.



Combined SE600 pH/EC/TDS Probe

The pH electrode utilizes a fiber junction to reduce contamination when measuring fertilizer solutions.



Accessories

- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution, 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution, 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution, 20 mL sachet (25 pcs)
- M10031B** 1413 $\mu\text{S/cm}$ calibration solution, 20 mL sachet (25 pcs)

- M10032B** 1382 ppm calibration solution, 20 mL sachet (25 pcs)
- MA9015** Electrode storage solution, 230 mL bottle
- MA9016** Cleaning solution, 230 mL bottle
- SE600** pH/EC/TDS spare probe with 1 meter cable



Ordering Information

MW801 PRO is supplied complete with **SE600** combination pH/EC/TDS probe, 20 mL sachet pH 7.01 buffer solution, 20 mL 1413 $\mu\text{S/cm}$ sachet of calibration solution, 20 mL 1382 ppm sachet of calibration solution, 9V battery and instructions.

MW802 PRO is supplied complete with **SE600** combination pH/EC/TDS probe, 20 mL sachet pH 7.01 buffer solution, 20 mL 1413 $\mu\text{S/cm}$ sachet of calibration solution, 20 mL 1500 ppm sachet of calibration solution, 9V battery and instructions.

MW180 MAX

pH/ORP/EC/TDS/NaCl/Temperature Laboratory Bench Meter

- Years warranty 3
- LOG
- MEM
- USB
- ATC
- GLP
- Points 2
- Dual Display
- MULTI
- Self diagnostics
- CE



MW180 MAX is a compact and versatile bench meter with a user-friendly interface that can measure six different parameters – pH, ORP, EC, TDS (Total Dissolved Solids), percentage of salinity (NaCl%) and temperature – when paired with the respective probe.

pH calibration can be performed in up to 5-point (selectable between 7 standard calibration buffers and two custom buffers), to improve measurement reliability even when testing samples with wide differences in pH.

The auto-ranging feature for both EC and TDS measurements automatically sets the most suitable resolution for the tested sample. All measurements can be automatically (ATC) or manually temperature compensated (MTC) with a user-selectable compensation coefficient. The temperature compensation can be disabled if the actual conductivity value is required (No TC).

MW180 MAX has GLP data review and the data can be transferred to a PC through a USB port.

A unique device identity code protects against the risks of loss and misuse.

Specifications	MW180 MAX
Range	pH -2.00 to 20.00 pH; -2.000 to 20.000 pH ORP ±2000 mV EC 0.00 to 29.99 µS/cm; 30.0 to 299.9 µS/cm; 300 to 2999 µS/cm; 3.00 to 29.99 mS/cm; 30.0 to 200.0 mS/cm; up to 500.0 mS/cm (absolute cond.*) TDS 0.0 to 14.99 mg/L (ppm); 15.0 to 149.9 mg/L (ppm); 150 to 1499 mg/L (ppm); 1.50 to 14.99 g/L (ppt); 15.0 to 100.0 g/L (ppt); up to 400.0 g/L absolute TDS* (with 0.80 factor) Salinity 0.0 to 400.0% NaCl, 2.00 to 42.00 PSU, 0.00 to 80.00 g/L Temp -20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	pH 0.01 pH; 0.002 pH ORP 0.1 mV EC 0.01 µS/cm; 0.1 µS/cm; 1 µS/cm; 0.01 mS/cm; 0.1 mS/cm; TDS 0.01 mg/L; 0.1 mg/L; 1.0 mg/L; 0.01 g/L; 0.1 g/L Salinity 0.1% NaCl, 0.01 PSU, 0.01 g/L Temp 0.1°C / 0.1°F
Accuracy	pH ±0.01 pH; ±0.002 pH ORP ±1 mV EC ±1% of reading ±(0.05 µS/cm or 1 digit) TDS ±1% of reading ±(0.03 ppm or 1 digit) Salinity ±1% reading Temp ±0.5°C / ±0.9°F
Temperature Compensation	ATC – automatic, from -20 to 120 °C (-4 to 248 °F) MTC – manual, from -20 to 120 °C (-4 to 248 °F) NO TC – without temperature compensation
Temperature Coefficient	0.00 to 6.00%/°C (EC and TDS only)
TDS Factor	0.40 to 0.80 (default value is 0.50)
Logging memory	Two independent storage spaces. Each save location can contain max. 1000 log records (stored in up to 100 lots). On demand, 200 logs; on stability, 200 logs; interval logging, 1000 logs
pH Electrode	MA917B/1 (included)
EC/TDS/NaCl/Temp. Probe	MA814DB/1 (included)
Temperature probe	MA831R
PC connectivity	1 USB port, 1 micro USB port
Power supply	12 VDC adapter (included)
Battery type	internal
Battery life	8 hours
Environment	0 to 50°C; max RH 95%
Packaging dimensions	335 x 120 x 255 mm
Packaging weight	2.44 kg

(*) Absolute conductivity (or TDS) is the conductivity (or TDS) value without temperature compensation



Accessories

- MA9004** pH 4.01 buffer, 230 mL bottle
- MA9007** pH 7.01 buffer, 230 mL bottle
- MA9010** pH 10.01 buffer, 230 mL bottle
- MA9015** Electrode storage solution, 230 mL bottle
- MA9016** Electrode cleaning solution, 230 mL bottle
- MA9112** pH 12.45 buffer solution, 230 mL bottle
- MA9060** 12880 µS/cm calibration solution, 230 mL bottle
- MA9061** 1413 µS/cm calibration solution, 230 mL bottle
- MA9063** 84 µS/cm calibration solution, 230 mL bottle
- MA9065** 111.8 mS/cm calibration solution, 230 mL bottle
- MA9066** 100% NaCl calibration solution, 230 mL bottle
- MA9069** 5000 µS/cm solution, 230 mL bottle
- MA9310** 12 VDC Adapter, 220 V
- MA9311** 12 VDC Adapter, 110 V
- MA9315** Electrode Holder
- MA917B/1** Double junction refillable pH electrode
- MA814DB/1** EC/TDS/NaCl/Temperature probe with DIN connector and 1 m cable
- MA924B/1** ±2000 mV Glass ORP electrode, refillable with BNC connector and 1 meter cable
- SE300** Platinum ORP electrode with 1 meter cable
- MA831R** Temperature probe
- MA9350** RS232 connection cable with 2 meters cable

Ordering Information

- MW180 MAX** is supplied complete with
- MA917B/1 pH Electrode
 - MA814DB/1 EC/TDS/NaCl/Temperature probe
 - MA831R Temperature Probe
 - M10004 pH 4.01 Sachet Buffer solution

- M10007 pH 7.01 Sachet Buffer solution
- M10010 pH 10.01 Sachet Buffer solution
- M10031 1413 µS/cm calibration solution
- M10016 Sachet Electrode Cleaning solution
- MA9315 Electrode Holder

- Graduated pipette
- 12 VDC adapter
- USB cable
- Instrument quality certificate
- Instruction manual

MW805 MAX/MW806 MAX



Portable pH/EC/TDS/Temperature Meters

MW805 MAX and MW806 MAX portable meters combine the main features of a benchtop unit into a portable, water-resistant meter that can measure up to 4 different parameters — pH, EC (Conductivity), TDS (Total Dissolved Solids), and temperature.

- Easy to read LCD display
- Auto-off feature to prolong battery life
- Internal clock and date to keep track of time-dependent functions (calibration timestamp, calibration time out)
- Up to 5-point pH calibration (selection from 7 standard calibration buffers and 2 custom buffers)
- Automatically (ATC) or manually temperature compensated (MTC) measurements, with a user-selectable compensation coefficient
- Available log space for up to 1000 records
- Logged data can be exported using a micro USB cable
- Dedicated GLP key to store and recall data on system status



- Years warranty **2**
- ATC
- Points **2**
- Dual Display
- MULTI
- Self diagnostics
- CE

Specifications	 MW805 MAX	 MW806 MAX
Range	pH -2.00. to 20.00 pH EC 0 to 4000 µS/cm TDS 0 to 2000 ppm (up to 3200 ppm with TDS 0.80 factor)	pH -2.00. to 20.00 pH EC 0.00 to 20.00 mS/cm TDS 0.00 to 10.00 ppt (up to 16.00 ppt with TDS 0.80 factor)
Resolution	pH 0.01 pH EC 1 µS/cm TDS 1 ppm Temp. 0.1°C	pH 0.01 pH EC 0.1 mS/cm TDS 0.01 ppt Temp. 0.1°C
Accuracy (@25°C)	pH ±0.01 pH EC/TDS ±2% Full Scale Temp. ±0.5°C	pH ±0.01 pH EC/TDS ±2% Full Scale Temp. ±0.5°C
Temperature compensation	ATC - automatic, from -20 to 120 °C MTC - manual, from -20 to 120 °C	ATC - automatic, from -20 to 120 °C MTC - manual, from -20 to 120 °C
pH Calibration	Up to 5-point automatic pH calibration, 7 standard buffers, 2 custom buffers	Up to 5-point automatic pH calibration, 7 standard buffers, 2 custom buffers
EC/TDS Calibration	Single cell factor calibration, 2 standards One-point offset: 0.00 µS/cm	Single cell factor calibration, 3 standards One-point offset: 0.00 µS/cm
Conductivity temp. coeff.	0.00 to 6.00%/°C	0.00 to 6.00%/°C
TDS Factor	0.40 to 0.80	0.40 to 0.80
Probe (included)	MA852 amplified pH/EC/TDS/Temp probe with DIN connector and 1 m cable	MA852 amplified pH/EC/TDS/Temp probe with DIN connector and 1 m cable
Logging memory	Up to 1000 log records On demand, up to 200 logs On stability, up to 200 logs Interval logging, up to 1000 logs Parameter-specific log store location	Up to 1000 log records On demand, up to 200 logs On stability, up to 200 logs Interval logging, up to 1000 logs Parameter-specific log store location
PC connectivity	1 micro USB port	1 micro USB port
Environment	0 to 50°C max RH 95%	0 to 50°C max RH 95%
Battery Type	3 x 1.5V alkaline AA (included)	3 x 1.5V alkaline AA (included)
Battery Life	approx. 200 hours of use	approx. 200 hours of use
Packaging dimensions	305 x 280 x 115 mm	305 x 280 x 115 mm
Packaging weight	1.44 kg	1.46 kg

Accessories



- MA852** Amplified pH/EC/TDS/Temperature probe with DIN connector and 1 m cable
- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9006** pH 6.86 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle
- MA9009** pH 9.18 buffer solution, 230 mL bottle
- MA9010** pH 10.01 buffer solution, 230 mL bottle
- MA9015** Probe storage solution, 230 mL
- MA9016** General cleaning solution, 230 mL
- MA9060** 12880 µS/cm solution, 230 mL
- MA9061** 1413 µS/cm solution, 230 mL
- M10000B** Rinse solution, 20 mL (25 pcs.)

Ordering Information

MW805 MAX is supplied complete with MA852 pH/EC/TDS/Temp amplified probe with 1 meter cable, 2x20 mL pH 4.01 and pH 7.01 sachet of calibration solutions, 2x20 mL 1413 µS/cm sachet of calibration solutions, 2x20 mL sachet of electrode cleaning solutions, rugged carrying case, batteries, micro USB cable and instructions.

MW806 MAX is supplied complete with MA852 pH/EC/TDS/Temp amplified probe with 1 meter cable, 2x20 mL pH 4.01 and pH 7.01 sachet of calibration solutions, 2x20 mL 12880 µS/cm sachet of calibration solutions, 2x20 mL sachet of electrode cleaning solutions, rugged carrying case, batteries, micro USB cable and instructions.

- Years warranty 2
- ATC
- IP65
- Points 2
- AUTO Buffer
- Dual Display
- Self diagnostics
- CE
- Electrode Replaceable



pH/EC/TDS/Temp Sensor

The MW803 MAX and MW804 MAX's exposed temperature sensor provides fast response time, and its proximity to the conductivity probe guarantees much more accurate temperature compensated readings.



MW803 MAX/MW804 MAX

pH/Conductivity/TDS/Temperature Testers with replaceable electrode

The MW803 MAX and MW804 MAX are water-resistant testers with dual-level LCD that measure pH/Conductivity/TDS/Temperature in one single tester!

The large display shows readings in an extended range from 0.00 to 14.00 pH and 0 to 3999 μ S/cm, 0 to 2000 ppm (MW803), 0 to 20.00 mS/cm, 0 to 10.00 ppt (MW804) and simultaneously shows temperature from 0.0 to 50.0°C or 32.0 to 122.0°F. They have a stability indicator and hold function that freezes the display for easy and accurate recording. The large display also has graphic symbols to guide you through all operations. The EC/TDS conversion factor is user selectable as well as the temperature compensation coefficient (β).

Ideal for quick and accurate measurements in swimming pools, aquariums and horticultural applications they can also be used in Industrial and Laboratory applications such as cooling towers, food processing, plating, drinking and waste water etc.

Specifications	 MW803 MAX	 MW804 MAX
Range	pH 0.00 to 14.00 pH EC 0 to 3999 μ S/cm TDS 0 to 2000 ppm Temp. 0.0 to 50.0°C / 32.0 to 122.0°F	0.00 to 14.00 pH 0 to 20.00 mS/cm 0 to 10.00 ppt 0.0 to 50.0°C / 32.0 to 122.0°F
Resolution	pH 0.01 pH EC 1 μ S/cm TDS 1 ppm Temp. 0.1°C / 0.1°F	0.01 pH 0.01 mS/cm 0.01 ppt 0.1°C / 0.1°F
Accuracy (@25°C)	pH \pm 0.05 pH EC/TDS \pm 2% Full scale Temp. \pm 0.5°C / \pm 1°F	\pm 0.05 pH \pm 2% Full scale \pm 0.5°C / \pm 1°F
Temperature Compensation	automatic with $\beta=0.0$ to 2.4%/°C	automatic with $\beta=0.0$ to 2.4%/°C
Calibration	automatic, 1 point for EC and 1 or 2 points for pH	automatic, 1 point for EC and 1 or 2 points for pH
TDS Factor	0.45 to 1.00 (conv.)	0.45 to 1.00 (conv.)
Probe	Mi60P (replaceable)	Mi60P (replaceable)
Environment	0 to 50°C; 100% RH max.	0 to 50°C; 100% RH max.
Battery Type	4 x 1.5V; IEC LR44, A76 (included)	4 x 1.5V; IEC LR44, A76 (included)
Battery Life	approx. 100 hours of use	approx. 100 hours of use
Auto-off	after 8 minutes of non-use	after 8 minutes of non-use
Packaging dimensions	254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight	220 g	220 g

Accessories

- Mi60P** Replaceable probe for MW803 & MW804
- M10000B** Rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)
- M10016B** Cleaning solution, 20 mL sachet (25 pcs)
- M10030B** 12880 μ S/cm calibration solution, 20 mL sachet, 25 pcs
- M10031B** 1413 μ S/cm calibration solution, 20 mL sachet, 25 pcs
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL sachet, (25 pcs)

- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL sachet, (25 pcs)
- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9006** pH 6.86 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle
- MA9009** pH 9.18 buffer solution, 230 mL bottle
- MA9010** pH 10.01 buffer solution, 230 mL bottle
- MA9015** Electrode storage solution, 230 mL
- MA9060** 12880 μ S/cm calibration solution, 230 mL bottle
- MA9061** 1413 μ S/cm calibration solution, 230 mL bottle
- MA9062** 1382 ppm calibration solution, 230 mL bottle
- MA753** Hard carrying case for 2 testers



Replaceable probe

Replace the probe in a fast and simple way yourself! Just unscrew the plastic ring on the top of the probe and replace the probe with a new one.

Battery life

Percentage of battery power remaining will be displayed upon startup.





MC810 MAX/MC811 MAX pH/EC/TDS/Temperature Monitors

The **MC810 MAX** and **MC811 MAX** monitors provide measurement and 24 hour continuous tracking of pH, conductivity (TDS with MC810 MAX and EC with MC811 MAX) and temperature. Quick to setup and simple to use, these monitors can be calibrated at one or two points for pH, and at one point for TDS (**MC810 MAX**) or EC (**MC811 MAX**). Results are monitored with 3 large LCD readouts, for simultaneous display of all three main parameters, and the temperature range is factory calibrated. The unit can be mounted above the sample to be tested or rested on a flat surface next to the sample, and the 2 m probes cable length allows for a correct positioning and adequate viewing. An external switch atop the **MC810 MAX** converts EC conductivity to TDS (ppm) using a fixed 0.5 or 0.7 conversion factor.

Features include:

- Easy Manual Calibration
- No Buttons to Program
- No Waiting for Software Confirmation
- Easy Wall Bracket Set-up (Brackets Included)
- Backlit LCD
- Two Point pH Calibration
- One Point TDS Calibration
- Replaceable pH Electrode
- "Easy Switch" TDS Conversion Technology Between 0.5 and 0.7



Specifications	 MC810 MAX	 MC811 MAX
Range	pH 0.0 to 12.0 pH EC/TDS 0 to 1990 ppm Temp. -10.0 to 60.0°C	pH 0.0 to 12.0 pH EC/TDS 0.00 to 5.00 mS/cm Temp. -10.0 to 60.0°C
Resolution	pH 0.1 pH EC/TDS 10 ppm Temp. 0.1°C	pH 0.1 pH EC/TDS 0.01 mS/cm Temp. 0.1°C
Accuracy (@25°C)	pH ±0.2 pH EC/TDS ±2% full scale Temp. ±0.3°C	pH ±0.2 pH EC/TDS ±2% full scale Temp. ±0.3°C
Calibration	pH manual, 2 points (trimmer) EC/TDS manual, 1 point (trimmer)	pH manual, 2 points (trimmer) EC/TDS manual, 1 point (trimmer)
pH electrode	MA911B/2 (replaceable)	MA911B/2 (replaceable)
EC probe	MA811 (fixed)	MA812 (fixed)
Temperature compensation	automatic from 5 to 50°C	automatic from 5 to 50°C
Power supply	12 VDC power adapter	12 VDC power adapter
Packaging dimensions	129 x 180 x 192 mm	129 x 180 x 192 mm
Packaging weight	1200 g	1165 g

Ordering Information:

The **MC810 MAX** and **MC811 MAX** monitors are supplied with:

- MA911B/2 pH electrode
- MA811 fixed TDS probe (MC810)
- MA812 fixed EC probe (MC811)
- Fixed temperature probe
- M10004 pH 4.01 buffer solution (sachet)
- M10007 pH 7.01 buffer solution (sachet)
- M10032 1382 ppm calibration solution (sachet) (MC810)
- M10442 1500 ppm calibration solution (sachet) (MC810)
- M10031 1413 µS/cm calibration solution (sachet) (MC811)
- M10016 Electrode cleaning solution (sachet, 2 pcs.)
- Calibration screwdriver
- 12 Vdc power adapter
- Instrument quality certificate
- Instruction manual

Accessories

- MA911B/2** Double junction, plastic body pH electrode with 2 m cable and BNC connector
- MA9004** pH 4.01 buffer solution, 230 mL
- MA9007** pH 7.01 buffer solution, 230 mL
- MA9010** pH 10.01 buffer solution, 230 mL
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL
- MA9061** 1413 µS/cm calibration solution, 230 mL
- MA9062** 1382 ppm TDS calibration solution, 230 ml
- M10004B** pH 4.01 buffer solution 20 mL sachet, 25 pcs
- M10007B** pH 7.01 buffer solution 20 mL sachet, 25 pcs
- M10010B** pH 10.01 buffer solution 20 mL sachet, 25 pcs
- M10016B** Electrode cleaning solution 20 mL sachet, 25 pcs
- M10031B** 1413 µS/cm calibration solution, 20 mL sachet, 25 pcs
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL sachet, 25 pcs
- M10442B** 1500 ppm (mg/L) calibration solution, 20 mL sachet, 25 pcs
- MA9310** 12 VDC Adapter, 220 V
- MA9311** 12 VDC Adapter, 110 V



MW700 PRO

Budget LUX Portable Meters for fast and reliable results

The microprocessor-based **MW700 PRO** is a portable Lux meter designed to perform light measurements. **MW700 PRO** has a small, ergonomic and light case design. Other features include large and easy to read LCD and long battery life.

These handy and ergonomically designed portable meters are ideal for anyone working on a low budget and still requires fast and reliable measurements. These portable meters are suitable for a wide range of applications, such as Educational, Agriculture and Horticulture, as well as water and environmental analysis.

Both models are supplied with a light sensor connected to the meter that measures from 0 to 50000 Lux. Average indoor lighting ranges from 100 to 1000 Lux and average outdoor sun lights about 50000 Lux. Lux is a unit that indicates the density of light that falls on a surface.

The light is necessary for the development of the plants. In fact, it is necessary a sufficient contribution of light in order to favor the photosynthesis and the closing of the plants.

The supplement of light by means of lamps electrical workers is the method simpler and economic in order to bring the necessary light to the plants.

The human eye is sensitive only to blue, green, and red light, so in calculating the Lux falling on an object, only the light that the human eye sees is counted. When only infrared light falls on an object, the Lux is counted as zero since our eyes see nothing. Mathematically, a spectral weighting function becomes convolved with the actual illumination spectrum to calculate Lux exactly.

This is the formal definition of Lux and it makes Lux an unusual unit of measure.

Still, Lux can be thought of as a way of measuring light in terms of what our eyes perceive. The metric unit of measure for luminance of a surface. One Lux is equal to one Lumen per square meter. One Lux equals 0.0929 footcandles.



Specifications	MW700 PRO
Range	0.000 to 1999 Lux 2000 to 19999 Lux 20000 to 50000 Lux
Range setting	manual through key buttons
Resolution	1 Lux 10 Lux 100 Lux
Accuracy	±6% of reading ±1 digit
Peak wave length	560 nm
Sensor Type	silicon photodiode
Sensor Sensitivity	100 scotopic Lux
Sensor stability	±2% change per year (in the first two years)
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Battery type	1x9V (IEC 6LR61) alkaline
Battery life	approximately 150 hours of continuous use
Auto-off	after about 5 minutes of non-use
Packaging dimensions	212 x 145 x 67 mm
Packaging weight	400 g

Ordering Information

MW700 PRO is supplied complete with 9V battery and instructions in a carton box.

Range keys

Press one of the three "Range keys" to select the proper scale according to the intensity of the light.



MI411 PRO

Free & Total Chlorine and pH Photometer

This latest laboratory grade microprocessor photometer has an excellent repeatability and is ideal for field measurements.

Chlorine is the most commonly used water disinfectant. Applications vary from treatment of drinking water and wastewater to pool and spa sanitization and food processing to sterilization.

The **MI411 PRO** is a portable microprocessor based instrument to measure three critical parameters to ensure good water quality: pH, free chlorine and total chlorine.

This instrument provides greater resolution, better accuracy and immediate results.

MI411 PRO is supplied in a hard carrying case including 2 cuvettes, reagents for 100 tests, wiping tissue and instruction manual.

**3 in 1 Combination
Photometer!**



Hard Carrying Case

MI411 PRO comes complete in hard carrying case making it ideal for field measurements.

Specifications		MI411 PRO
Range	Free Chlorine Total Chlorine pH	0.00 to 5.00 mg/L Cl ₂ 0.00 to 5.00 mg/L Cl ₂ 6.5 to 8.0 pH
Resolution	Free Chlorine Total Chlorine pH	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L) 0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L) 0.1 pH
Accuracy	Free Chlorine Total Chlorine pH	±0.06 mg/L @ 1.50 mg/L ±0.06 mg/L @ 1.50 mg/L ±0.1 pH @ 7.2 pH
Method	Free Chlorine Total Chlorine pH	adaptation of the USEPA method 330.5 and Standard Method 4500-Cl G adaptation of the USEPA method 330.5 and Standard Method 4500-Cl G adaptation of the phenol red method
Light Source		tungsten lamp
Light Detector		silicon photocell and 525 nm narrow band interference filter
Environment		0 to 50°C / 32 to 122°F; max RH 100%
Battery Type		1 x 9V
Auto-off		after 10 minutes of non use
Packaging dimensions		305 x 280 x 115 mm
Packaging weight		1.26 kg



Accessories

- Mi504-100** Free & Total Chlorine reagent set (100 tests)
- Mi509-100** pH reagent (100 tests)
- Mi511-100** Free & Total Chlorine and pH reagent set (100 tests)
- Mi524-100** Total Chlorine powder reagents (100 tests)
- Mi526-100** Free Chlorine powder reagents (100 tests)



- Mi0001** Glass cuvettes (2 pcs)
- Mi0002** Caps for cuvettes (2 pcs)
- Mi0003** Stoppers for cuvettes (2 pcs)

Ordering Information

MI411 PRO is supplied complete with 2 cuvettes, Mi511-100 liquid reagents for 100 tests, hard carrying case, wiping tissue, 9V battery and instructions.

MI405 PRO/MI407 PRO/MI408 PRO/MI412 PRO Ammonia, Iron & Phosphate Photometers

These user-friendly Colorimeters will give you direct readings in mg/L.

Ammonia detection in water treatment systems is particularly important for aquarium owners and fish farm operators.

Ammonia is highly soluble in water and extremely toxic to fish. Fish farm owners must monitor and maintain careful control of ammonia levels to ensure optimum water conditions for their stock.

Milwaukee offers 2 instruments for low and medium concentrations: **MI405 PRO** with a range of 0.00 to 9.99 mg/L and **MI407 PRO** from 0.00 to 3.00 mg/L.

Iron is naturally present in water supplies and its presence in both potable and industrial applications is regarded as objectionable. Milwaukee offers **MI408 PRO** Iron meter with a range of 0.00 to 5.00 mg/L.

Phosphates are present in natural waters and at concentrations typically found, do not pose any specific health threats to humans.

However, excessive contamination of water courses from agricultural fertilizer run off or wastewater/effluent discharge can promote excessive algae or plant growth. Milwaukee offers **MI412 PRO** with range 0.00 to 2.50 mg/L.



Specifications		 MI405 PRO Ammonia MR	 MI407 PRO Ammonia LR	 MI408 PRO Iron HR	 MI412 PRO Phosphate LR
Range	Ammonia Iron Phosphate	0.00 to 9.99 mg/L (NH ₃ -N)	0.00 to 3.00 mg/L (NH ₃ -N)	0.00 to 5.00 mg/L (Fe)	0.00 to 2.50 mg/L (PO ₄)
Resolution	Ammonia Iron Phosphate	0.01 mg/L	0.01 mg/L	0.01 mg/L	0.01 mg/L
Accuracy	Ammonia Iron Phosphate	±0.30 mg/L @5.00 mg/L	±0.09 mg/L @1.50 mg/L	±0.06 mg/L @1.50 mg/L	±0.07 mg/L @1.00 mg/L
Method		adaptation of Nessler method	adaptation of Nessler method	adaptation of the USEPA method 315 B and Standard method 3500 - Fe B	adaptation of the Ascorbic Acid method
Light Source		Blue LED 466 nm	Blue LED 466 nm	tungsten lamp	tungsten lamp
Light Detector		silicon photocell and 466 nm narrow band interference filter	silicon photocell and 466 nm narrow band interference filter	silicon photocell and 525 nm narrow band interference filter	silicon photocell and 610 nm narrow band interference filter
Environment		0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%
Battery Type		1 x 9 V	1 x 9 V	1 x 9 V	1 x 9 V
Auto-off		after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use
Packaging dimensions		305 x 280 x 115 mm	305 x 280 x 115 mm	305 x 280 x 115 mm	305 x 280 x 115 mm
Packaging weight		1.24 kg	1.22 kg	1.22 kg	1.3 kg

Accessories

- Mi505-100** Ammonia MR liquid reagent (100 tests)
- Mi507-100** Ammonia LR liquid reagent (100 tests)
- Mi508-100** Iron HR liquid reagent (100 tests)
- Mi512-100** Phosphate LR powder reagent (100 tests)

- Mi0001**
- Mi0002**
- Mi0003**

- Glass cuvettes (2 pcs)
- Caps for cuvettes (2 pcs)
- Stoppers for cuvettes (2 pcs)



Ordering Information

MI405 PRO, MI407 PRO, MI408 PRO and **MI412 PRO** are supplied complete with 2 cuvettes, reagents for 100 tests, hard carrying case, wiping tissue, 9V battery and instructions.



MI404 PRO/MI406 PRO/MI413 PRO/MI414 PRO

Free & Total Chlorine and Chloride Photometers

Milwaukee provides a range of chlorine photometers for all applications: swimming pool treatments, household cleaners, dishwasher additives, laundry powders/liquids and cooling water treatment products all contain chlorine as an oxidizing biocide. Drinking water contains residual chlorine to maintain water purity throughout the supply lines.

Milwaukee offers 3 microprocessor-based instruments with greater resolution, better accuracy and immediate results.

You can choose between three different models: **MI404 PRO** for measuring free (0.00 to 5.00 mg/L) and total (0.00 to 5.00 mg/L) chlorine, **MI406 PRO** for measuring free (0.00 to 5.00 mg/L) chlorine and **MI413 PRO** for measuring free (0.00 to 10.00 mg/L) and total (0.00 to 10.00 mg/L) chlorine.



Chloride is a major constituent of sea water and is extremely corrosive in acidic environments. It requires close monitoring in applications such as marine boiler systems that are effected by seawater contamination.

Chlorides are used by the water treatment professional to determine cycles of concentration in low pressure boilers and cooling systems.

It is essential to monitor chloride concentrations in boiler systems to prevent metal parts being damaged. In high levels, chloride can corrode stainless steel.

Milwaukee offers the **MI414 PRO** microprocessor-based photometer for measuring chloride (0.00 to 20.00 mg/L).

Specifications		 MI404 PRO Free & Total Chlorine	 MI406 PRO Free Chlorine	 MI413 PRO Free & Total Chlorine HR	 MI414 PRO Chloride
Range	Free Chlorine Total Chlorine Chloride	0.00 to 5.00 mg/L (Cl ₂) 0.00 to 5.00 mg/L (Cl ₂)	0.00 to 5.00 mg/L (Cl ₂)	0.00 to 10.00 mg/L (Cl ₂) 0.00 to 10.00 mg/L (Cl ₂)	0.00 to 20.00 mg/L (Cl ⁻)
Resolution	Free Chlorine Total Chlorine Chloride	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L) 0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L) 0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L
Accuracy	Free Chlorine Total Chlorine Chloride	±0.06 mg/L @1.50 mg/L ±0.06 mg/L @1.50 mg/L	±0.06 mg/L @1.50 mg/L	±0.17 mg/L @1.50 mg/L ±0.17 mg/L @1.50 mg/L	±1.0 mg/L @10.0 mg/L
Method		adaptation of USEPA method 330.5 and Standard Method 4500-Cl G	adaptation of USEPA method 330.5 and Standard Method 4500-Cl G	adaptation of USEPA method 330.5 and Standard Method 4500-Cl G	adaptation of mercury (II) thiocyanate method
Light Source		tungsten lamp	tungsten lamp	tungsten lamp	Blue LED 466 nm
Light Detector		silicon photocell and 525 nm narrow band interference filter	silicon photocell and 525 nm narrow band interference filter	silicon photocell and 525 nm narrow band interference filter	silicon photocell and 466 nm narrow band interference filter
Environment		0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%
Battery Type		1 x 9 V	1 x 9 V	1 x 9 V	1 x 9 V
Auto-off		after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use
Packaging dimensions		305 x 280 x 115 mm	305 x 280 x 115 mm	305 x 280 x 115 mm	305 x 280 x 115 mm
Packaging weight		1.24 kg	1.26 kg	1.52 kg	1.44 kg

Accessories

- Mi504-100** Free & Total Chlorine liquid reagent set (100 tests)
- Mi506-100** Free Chlorine liquid reagent set (100 tests)
- Mi513-045** Free & Total Chlorine liquid reagent set (45 tests)
- Mi514-100** Chloride liquid reagent set (100 tests)



- Mi524-100** Total Chlorine powder reagents (100 tests)
- Mi526-100** Free Chlorine powder reagents (100 tests)
- Mi0001** Glass cuvettes (2 pcs)
- Mi0002** Caps for cuvettes (2 pcs)
- Mi0003** Stoppers for cuvettes (2 pcs)

Ordering Information

MI404 PRO, MI406 PRO, MI413 PRO and MI414 PRO are supplied complete with 2 cuvettes, reagents, hard carrying case, wiping tissue, 9V battery and instructions.

MW10/MW11

Low cost digital photometers to measure Free & Total Chlorine

Chlorine is the most commonly used water disinfectant. Applications vary from treatment of drinking water and wastewater to pool and spa sanitization and food processing to sterilization.

Milwaukee offers 2 models:

MW10 for measuring free chlorine (0.00 to 2.50 mg/L)

MW11 to measure total chlorine (0.00 to 3.50 mg/L).

Key features include:

- User friendly;
- Small & Ergonomic case design;
- Inexpensive;
- Large and easy to read display;
- Good accuracy and immediate results;

- Years warranty 2
- Self diagnostics
- LED
- CE



Specifications	MW10 Free chlorine	MW11 Total chlorine
Range	0.00 to 2.50 ppm	0.00 to 3.50 ppm
Resolution	0.01 ppm	0.01 ppm
Accuracy (@25°C)	±0.03 ppm ±3% of reading	±0.03 ppm ±3% of reading
Typical EMC Dev.	±0.01 ppm	±0.01 ppm
Light Source	Light Emitting Diode @ 525 nm	Light Emitting Diode @ 525 nm
Light Detector	Silicon Photocell	Silicon Photocell
Method	Adaptation of USEPA method 330.5. The reaction between free chlorine and the DPD reagent causes a pink tint in the sample.	Adaptation of USEPA method 330.5. The reaction between free chlorine and the DPD reagent causes a pink tint in the sample.
Environment	0 to 50°C (32 to 122°F) max. 95% RH non-condensing	0 to 50°C (32 to 122°F) max. 95% RH non-condensing
Battery Type	1 x 1.5V AAA	1 x 1.5V AAA
Auto-off	after 2 minutes of non use	after 2 minutes of non use
Packaging dimensions	115 x 115 x 84 mm	115 x 115 x 84 mm
Packaging weight	180 g	180 g



Accessories

- Mi526-25** Free Chlorine powder reagent, (25 pcs)
- Mi0011** Glass cuvetts (2 pcs)
- Mi524-25** Total Chlorine powder reagent (25 pcs)
- Mi0013** Stoppers for cuvetts (2 pcs)

Ordering information:

All handy photometers are supplied in a carton box including 2 cuvetts, 6 powder reagents, 1 x 1.5 V AAA battery and instructions.

The handy photometers are supplied in a carton box including all accessories.

MW12/MW13/MW14

Low cost digital photometers to measure Phosphate, Iron & Iodine

Iron is naturally present in water supplies and therefore needs to be monitored both in potable and industrial applications. Milwaukee offers the **MW14** Iron meter with a range of 0.00 to 5.00 mg/L.

Phosphates are present in natural waters and at concentrations typically found, do not pose any specific health threats to humans. However, excessive contamination of water courses from agricultural fertilizer run off or wastewater / effluent discharge can promote excessive algae or plant growth.

Milwaukee offers **MW12** with a range of 0.00 to 2.50 mg/L.

Iodine is used as disinfectant in various applications - one of the most common is the poultry industry waste water treatment.

Milwaukee offers **MW13** with a range of 0.0 to 12.5 mg/L.



Specifications	MW12 Phosphate	MW13 Iodine	MW14 Iron
Range	0.00 to 2.50 ppm	0.0 to 12.5 ppm	0.00 to 5.00 ppm
Resolution	0.01 ppm	0.1 ppm	0.01 ppm
Accuracy (@25°C)	±0.04 ppm ±4% of reading	±0.1 ppm ±5% of reading	±0.04 ppm ±2% of reading
Typical EMC Dev.	±0.01 ppm	±0.1 ppm	±0.01 ppm
Light Source	LED @ 525 nm	LED @ 525 nm	LED @ 525 nm
Light Detector	Silicon Photocell	Silicon Photocell	Silicon Photocell
Method	Adaptation of the Standard Methods for the Examination of Water and Wastewater, 20th edition, Ascorbic Acid method. The reaction between phosphate and the reagent causes a blue tint in the sample.	Adaptation of the Standard Methods for the Examination of Water and Wastewater, 18th edition, DPD method. The reaction between iodine and the reagent causes a pink tint in the sample.	Adaptation of the EPA Phenanthroline method 315B, for natural and treated waters. The reaction between iron and reagent causes an orange tint in the sample.
Environment	0 to 50°C (32 to 122°F) max 95% RH non-condensing	0 to 50°C (32 to 122°F) max 95% RH non-condensing	0 to 50°C (32 to 122°F) max 95% RH non-condensing
Battery Type	1 x 1.5V AAA	1 x 1.5V AAA	1 x 1.5V AAA
Auto-off	after 2 minutes of non use	after 2 minutes of non use	after 2 minutes of non use
Packaging dimensions	115 x 115 x 84 mm	115 x 115 x 84 mm	115 x 115 x 84 mm
Packaging weight	180 g	180 g	180 g

Accessories

- Mi512-25** Phosphate powder reagent (25 pcs)
- Mi527-25** Iodine powder reagent (25 pcs)
- Mi528-25** Iron powder reagent (25 pcs)

- Mi0011** Glass cuvetts (2 pcs)
- Mi0013** Stoppers for cuvetts (2 pcs)

Ordering information:

All handy photometers are supplied in a carton box including 2 cuvetts, 6 powder reagents, 1 x 1.5 V AAA battery and instructions.



MI490

Peroxide Value Photometer for Edible Oils

MI490 is a user-friendly photometer for monitoring peroxide value in the process of oil making. This instrument will give you direct readings, with a range of 0.0 to 25.0 meq O₂/Kg .

The measurement of the oil's chemical degradation is the peroxide value, which measures the degree to which the oil is oxidized. Rancidification is the decomposition of fats and other lipids by hydrolysis and/or oxidation. Hydrolysis will split fatty acid chains away from the glycerol backbone in glycerides. These free fatty acids can then undergo further auto-oxidation. Oxidation primarily occurs with unsaturated fats by a free radical-mediated process.

One of the most widely used tests for oxidative rancidity, peroxide value is a measure of the concentration of peroxides and hydroperoxides formed in the initial stages of lipid oxidation. Milliequivalents of peroxide per kg of fat are measured by titration with iodide ion.

Peroxide values are not static and care must be taken in handling and testing samples. It is difficult to provide a specific guideline relating peroxide value to rancidity. High peroxide values are a definite indication of a rancid fat, but moderate values may be the result of depletion of peroxides after reaching high concentrations.

Easy Steps

Prepare the sample with oil and the reagent then insert it in the instrument and note the reading.



Accurate Readings

MI490 will give you direct readings, with a range of 0.0 to 25.0 meq O₂/Kg in the process of oil making.



Specifications	MI490 Peroxide Value
Range	0.0 to 25.0 meq O ₂ /Kg
Resolution	0.5 meq O ₂ /Kg
Accuracy	±0.5 meq O ₂ /Kg
Method	adaptation of the CE n. 2568/97 method
Environment	0 to 50°C; max RH 95%
Battery Type	4 x 1.5V AA
Auto-off	after 15 minutes of non-use
Packaging dimensions	340 x 260 x 118 mm
Packaging weight	1.76 kg



Accessories

MI590-021 Peroxides reagent set (21 tests)



Ordering Information

MI490 is supplied complete with: reagents for 20 tests, 4 x 1 mL syringe, tissue for wiping cuvetts, 4 x 1.5V AA batteries and instruction manual.

MI415 PRO Turbidity Meter

Turbidity refers to the concentration of undissolved, suspended particles present in a liquid. Turbidity is a measure of the clarity of a sample. For potable water applications turbidity is a good indicator of water quality.

Turbidity Measurement is achieved by analyzing the amount of light refracted from suspended particles such as clay, silt and organic material.

By measuring turbidity, by photometric or tube methods, it is possible to estimate suspended solids content.

MI415 PRO has two operating ranges; 0.00 to 50.00 FNU, and 50 to 1000 FNU that can accommodate the most turbid condition you may encounter.

MI415 PRO is supplied in a hard carrying case, complete with all accessories.



Specifications	MI415 PRO Turbidity meter
Range	0.00 to 50.00 FNU; 50 to 1000 FNU
Resolution	0.01 FNU; 1 FNU
Accuracy	±0.5 FNU or ±5% of reading, whichever is greater
Method	detection of scattered light
Light Source	high emission infrared LED
Light Detector	silicon photocell
Environment	0 to 50°C 32 to 122°F; max RH 100%
Battery Type	1 x 9V
Auto-off	after 5 minutes of non-use
Packaging dimensions	305 x 280 x 115 mm
Packaging weight	1.24 kg

Introduction to Turbidity

The cloudy appearance of water (called Turbidity) is caused by suspended material. The unit of measure adopted by the ISO Standard is the FNU (Formazine Nephelometric Unit) and by EPA is NTU (Nephelometric Turbidity Unit).

The other two methods used to test for turbidity and their measurement units are the JTU (Jackson Turbidity Unit) and the Silica unit (mg/L SiO₂).

See the conversion table of these methods and their units for your reference.

(mg/L)	JTU	FTU (NTU/FNU)	SiO ₂
JTU	1	19	2.5
FTU	0.053	1	0.13
SiO ₂	0.4	7.5	1

Accessories

Mi515-100 AMCO-AEPA-1 @ 0 FNU calibration solution, 30 mL
 AMCO-AEPA-1 @ 10 FNU, calibration solution, 30 mL
 AMCO-AEPA-1 @ 500 FNU, calibration solution, 30 mL



Mi0011 Glass cuvettes (2 pcs)
Mi0012 Caps for cuvettes (2 pcs)
Mi0013 Stoppers for cuvettes (2 pcs)

Ordering Information

MI415 PRO is supplied complete with 2 cuvettes, calibration solutions, hard carrying case, wiping tissue, 9V battery and instructions.

MA871/MA872/MA873/MA881 Digital Refractometers for Brix, Fructose, Glucose and Invert Sugar Measurements



The digital refractometers are optical instruments that employ the measurement of refractive index to determine the % Brix of sugar (MA871), % Fructose (MA872), % Glucose (MA873) and % Invert Sugar (MA881) in aqueous solutions.

The method is both simple and quick. Samples are measured after a simple user calibration with deionized or distilled water. Within seconds the instruments measure the refractive index of the sample and convert it to % Brix or % by weight concentration units.

The digital refractometers eliminate the uncertainty associated with mechanical refractometers and are easily portable for measurements in the field. The measurement technique and temperature compensation employ methodology recommended in the ICUMSA Methods Book (Internationally recognized body for Sugar Analysis). Temperature (in °C or °F) is displayed simultaneously with the measurement on the large dual level display along with icons for Low Power and other helpful message codes.

Key features include:

- Dual-level LCD
- Automatic Temperature Compensation (ATC)
- Easy setup and storage
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use

Specifications	MA871 Brix	MA872 Fructose	MA873 Glucose	MA881 Invert Sugar
Range	0 to 85% Brix 0 to 80°C / 32 to 176°F	0 to 85% mass 0 to 80°C / 32 to 176°F	0 to 85% mass 0 to 80°C / 32 to 176°F	0 to 85% mass 0 to 80°C / 32 to 176°F
Resolution	0.1% Brix 0.1°C / 0.1°F	0.1% 0.1°C / 0.1°F	0.1% 0.1°C / 0.1°F	0.1% 0.1°C / 0.1°F
Accuracy	±0.2% Brix ±0.3°C / ±0.5°F	±0.2% ±0.3°C / ±0.5°F	±0.2% ±0.3°C / ±0.5°F	±0.2% ±0.3°C / ±0.5°F
Light source	yellow LED	yellow LED	yellow LED	yellow LED
Measurement Time	approximately 1.5 seconds	approximately 1.5 seconds	approximately 1.5 seconds	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)	100 µL (cover prism totally)	100 µL (cover prism totally)	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism	SS ring and flint glass prism	SS ring and flint glass prism	SS ring and flint glass prism
Temperature Compensation	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F
Case Material	ABS	ABS	ABS	ABS
Battery Type	1 x 9V AA (included)	1 x 9V AA (included)	1 x 9V AA (included)	1 x 9V AA (included)
Battery Life	5000 reading	5000 reading	5000 reading	5000 reading
Auto-shut off	after 3 minutes of non-use	after 3 minutes of non-use	after 3 minutes of non-use	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm	268 x 122 x 118 mm	268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight	660 g	663 g	666 g	644 g

Ordering Information

MA871, MA872, MA873 and MA881 are supplied in a carton box, complete with 9V battery, pipette and instruction manual. Optionally you can also order the refractometers in a hard carrying case (MA752).

Stainless Steel Sample Well and Prism

Place a few drops of the sample in the well and press the READ key.



MA882/MA883/MA884/MA885 Digital Refractometers for Grape Juice Must Measurements

The MA882, MA883, MA884 and MA885 are optical instruments that are based on the measurement of the refractive index of a solution. The measurement of refractive index is simple and quick and provides the vintner an accepted method for sugar content analysis. Samples are measured after a simple user calibration with deionized or distilled water. Within seconds the instrument measures the refractive index of the grape. This digital refractometers eliminate the uncertainty associated with mechanical refractometers and are easily portable for measurements in the field. The four instruments utilize internationally recognized references for unit conversion and temperature compensation.

Temperature (in °C or °F) is displayed simultaneously with the measurement on the large dual level display along with icons for Low Power and other helpful message codes.



Key features include:

- Dual-level LCD
- Easy setup and storage
- Automatic Temperature Compensation (ATC)
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use

- **MA882** measures %Brix;
- **MA883** measures °Baumé;
- **MA884** measures %Brix and Potential Alcohol (% vol);
- **MA885** measures %Brix, °Oechsle (°Oe) and °KMW (°Babo).

Specifications	 MA882	 MA883	 MA884	 MA885
Range	0 to 50% Brix 0 to 80°C / 32 to 176°F	0 to 28 °Baumé 0 to 80°C / 32 to 176°F	0 to 50% Brix 0 to 25% v/v Potential Alc. 0 to 80°C / 32 to 176°F	0 to 50% Brix 0 to 230 °Oechsle 0 to 42 °KMW 0 to 80°C / 32 to 176°F
Resolution	0.1% Brix 0.1°C / 0.1°F	0.1 °Baumé 0.1°C / 0.1°F	0.1% Brix 0.1% v/v Potential Alcohol 0.1°C / 0.1°F	0.1% Brix 1 °Oechsle 0.1 °KMW 0.1°C / 0.1°F
Accuracy	±0.2% Brix ±0.3°C / ±0.5°F	±0.1 °Baumé ±0.3°C / ±0.5°F	±0.2% Brix ±0.2 v/v Potential Alcohol ±0.3°C / ±0.5°F	±0.2% Brix ±1 °Oechsle ±0.2 °KMW ±0.3°C / ±0.5°F
Light Source	yellow LED	yellow LED	yellow LED	yellow LED
Measurement Time	approximately 1.5 seconds	approximately 1.5 seconds	approximately 1.5 seconds	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)	100 µL (cover prism totally)	100 µL (cover prism totally)	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism	SS ring and flint glass prism	SS ring and flint glass prism	SS ring and flint glass prism
Temperature Compensation	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F
Case Material	ABS	ABS	ABS	ABS
Battery Type	1 x 9V AA (included)	1 x 9V AA (included)	1 x 9V AA (included)	1 x 9V AA (included)
Battery Life	5000 reading	5000 reading	5000 reading	5000 reading
Auto-shut off	after 3 minutes of non-use	after 3 minutes of non-use	after 3 minutes of non-use	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm	268 x 122 x 118 mm	268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight	672 g	670 g	678 g	672 g

Ordering Information

MA882, MA883, MA884 and MA885 are supplied in a carton box, complete with 9V battery, pipette and instruction manual.

Optionally you can also order the refractometers in a hard carrying case (MA752).



MA886 Digital Refractometer for Sodium Chloride Measurements



The MA886 is an optical instrument that employs the measurement of the refractive index to determine sodium chloride concentration in aqueous solutions used in food preparation.

It is not intended for sea water salinity measurements.

The measurement of refractive index is simple and quick and provides the user an accepted method for NaCl analysis.

Samples are measured after a simple user calibration with deionized or distilled water. Within seconds the instrument measures the refractive index of the solution.

The digital refractometer eliminates the uncertainty associated with mechanical refractometers and is easily portable for measurements where you need them.

The instrument utilizes internationally recognized references for unit conversion and temperature compensation. It can display the measurement of NaCl concentration 4 different ways: g/100 g, g/100 mL, Specific Gravity, and °Baumé. Temperature (in °C or °F) is displayed simultaneously with the measurement (on 3 of the ranges) on the large dual level display along with icons for Low Power and other helpful message codes.

Key features include:

- Dual-level LCD
- Automatic Temperature Compensation (ATC)
- Easy setup and storage
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use

Specifications	MA886
Range	0 to 28 g/100 g 0 to 34 g/100 ml 1.000 to 1.216 Specific Gravity 0 to 26 °Baumé 0 to 80°C / 32 to 176°F
Resolution	0.1 g/100 g 0.1 g/100 ml 0.001 Specific Gravity 0.1 °Baumé 0.1°C / 0.1°F
Accuracy	±0.2 g/100 g ±0.2 g/100 ml ±0.002 Specific Gravity ±0.2 °Baumé ±0.3°C / ±0.5°F
Light Source	yellow LED
Measurement Time	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism
Temperature Compensation	automatic between 10 and 40°C (50 to 104°F)
Case Material	ABS
Battery Type	1 x 9V AA (included)
Battery Life	5000 reading
Auto-shut off	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm
Packaging weight	661 g



Stainless Steel Sample Well and Prism

Place a few drops of the sample in the well and press the READ key.

Liquid Crystal Display (LCD)

Dual Level LCD with Primary and Secondary Display.



Ordering Information

MA886 is supplied in a carton box, complete with 9V battery, pipette and instruction manual. Optionally you can also order the refractometers in a hard carrying case (MA752).



Measuring salt in cheese


Using MA886 Digital Sodium Chloride Refractometer

Sodium occurs naturally in many foods and is also added in the form of salt. The sodium content of food has important implications for health. Sodium is a nutrient and is part of the group of dietary minerals. Essential to life, it cannot be produced by the human body and thus has to be provided by the diet. The physiological requirements of sodium of the human body are relatively low (estimated at the equivalent of 1 to 2 gram of salt per day) and are met by the diet.



Fresh cheeses (non-salted) contain very little sodium (from 30 to 60 mg /100g). Hard cheeses – because of added salt – contain much higher levels of sodium (from 200 to 1600 mg/100g). Within a family of cheeses and depending on the brands, large variations exist between sodium contents of the cheeses, depending on lower or higher addition of salt by the cheese maker.

Measuring salt (sodium chloride) in cheese



1. Dicing:
Mincing the sample increases the surface area to allow as much salt to be released into the water as possible.



2. Dilution:
Dilute the sample with hot water to a 10% ratio.
After the sample melted, the fat will float to the top.


3. Collect the sample with a pipette from the layer underneath the fat

4. Using the plastic pipette, drip sample onto the prism surface. Fill the well completely.



5. Press the READ key.
The results are displayed in unit of interest

For optimal measurement put a sample into a beaker.



MA887

Digital Refractometer for Seawater Measurements



The **MA887** is an optical instrument that employs the measurement of the refractive index to determine the salinity of natural and artificial seawater, ocean water or brackish intermediates.

The digital refractometer eliminates the uncertainty associated with mechanical refractometers and is easily portable for ship, shore or home use.

The **MA887** refractometer is an optical device that is simple and quick to use. Samples are measured after a simple user calibration with distilled or deionized water. Within seconds, the refractive index and temperature are measured and converted into one of three popular measurement units; Practical Salinity Units (PSU), Salinity in parts per thousand (ppt), or Specific Gravity (S.G. (20/20)).

All conversion algorithms are based upon respected scientific publications using the physical properties of seawater (not sodium chloride). The temperature (in °C or °F) is also displayed on the large dual level display along with helpful message codes.

Key features include:

- Dual-level LCD
- Automatic Temperature Compensation (ATC)
- Easy setup and storage
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use

Specifications	MA887
Range	0 to 50 PSU 0 to 150 ppt 1.000 to 1.114 S.G. (20/20) 0 to 80°C / 32 to 176°F
Resolution	1 PSU 1 ppt 0.001 S.G. (20/20) 0.1°C / 0.1°F
Accuracy	±2 PSU ±2 ppt ±0.002 S.G. (20/20) ±0.3°C / 0.5°F
Light Source	yellow LED
Measurement Time	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism
Temperature Compensation	automatic between 0 and 40°C (50 to 104°F)
Case Material	ABS
Battery Type	1 x 9V AA (included)
Battery Life	5000 reading
Auto-shut off	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm
Packing weight	668 g



Stainless Steel Sample Well and Prism

Place a few drops of the sample in the well and press the READ key.

Liquid Crystal Display (LCD)

Dual Level LCD with Primary and Secondary Display.



Ordering Information

MA887 is supplied in a carton box, complete with 9V battery, pipette and instruction manual. Optionally you can also order the refractometers in a hard carrying case (**MA752**).



MA888

Digital Refractometer for Ethylene Glycol Measurements

The MA888 is an optical instrument that employs the measurement of the refractive index to determine the % volume and freezing point of ethylene glycol based coolants or antifreeze.

The digital refractometer eliminates the uncertainty associated with mechanical refractometers and is easily portable for use in the field to optimize your cooling system.

The MA888 refractometer is an optical device that is simple and quick to use. Samples are measured after a simple user calibration with distilled or deionized water. Within seconds, the refractive index and temperature are measured and converted into one of two measurement units; % Volume or Freezing Point.

The instrument utilizes internationally recognized references for unit conversion and temperature compensation for ethylene glycol solutions (e.g. CRC Handbook of Chemistry and Physics, 87th Edition).

The temperature (in °C or °F) is also displayed on the large dual level display along with helpful message codes.

Key features include:

- Dual-level LCD
- Automatic Temperature Compensation (ATC)
- Easy setup and storage
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use



- Years warranty 2
- ATC
- Dual Display
- Self diagnostics
- CE

Specifications	MA888
Range	0 to 100% Volume 0 to -50°C / 32 to -58°F Freezing Point 0 to 80°C / 32 to 176°F
Resolution	0.1% Volume 0.1°C / 0.1°F Freezing Point 0.1°C / 0.1°F
Accuracy	±0.2% Volume ±0.5°C / ±1.0°F Freezing Point ±0.3°C / ±0.5°F
Light Source	yellow LED
Measurement Time	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism
Temperature Compensation	automatic between 0 and 40°C (50 to 104°F)
Case Material	ABS
Battery Type	1 x 9V AA (included)
Battery Life	5000 reading
Auto-shut off	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm
Packaging weight	667 g



Stainless Steel Sample Well and Prism

Place a few drops of the sample in the well and press the READ key.



Liquid Crystal Display (LCD)

Dual Level LCD with Primary and Secondary Display.

Ordering Information

MA888 is supplied in a carton box, complete with 9V battery, pipette and instruction manual. Optionally you can also order the refractometers in a hard carrying case (MA752).





TH300/TH310 Pocket-sized thermometers with automatic calibration check

Scientists and laboratory technicians rely on the accuracy of their thermometers when performing routine measurements. For this reason, Milwaukee developed the **TH310**. This palm-sized unit is a highly accurate thermometer that is destined to make glass thermometers obsolete.

Remote temperature measurements require a versatile thermometer with a remote probe that can be used in a hard-to-reach places. The meter must also be easily readable at an angle. The **TH300** is equipped with a stainless steel general purpose probe and 1 meter cable to make remote reading a simple task.

The thermometers have easy-to-read display which shows clear readings at any angle.

Specifications	TH300	TH310
Range	-50.0 to 150.0°C	-50.0 to 150.0°C
Resolution	0.1°C	0.1°C
Accuracy (@20°C)	±0.5°C (-20 to 90°C)	±0.5°C (-20 to 90°C)
Typical EMC Deviation	±0.3°C	±0.3°C
Probe	Stainless steel with 1 meter cable	Stainless steel
Switch ON/OFF	no	yes
Calibration Check	no	yes
Environment	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%
Battery Type	1 x 1.4V	1 x 1.5V
Battery Life	approximately 1 year	approximately 3000 hours of continuous use
Packaging dimensions	225 x 91 x 47 mm	254 x 67 x 47 mm
Packaging weight	140 g	100 g

Ordering Information

TH300 is supplied with stainless steel probe with 1 meter cable, batteries and instruction manual.

TH310 is supplied with batteries and instruction manual.

MT6003 NPK Soil Test Kit



The primary nutrients essential to plant growth and quality are Nitrogen, Phosphorous and Potassium.

N is associated with plant growth above the ground, **P** is responsible for flower and fruit production as well as overall plant health. **K** helps disease resistance, water intake and strong root growth.

This kit provides accurate and professional tests and includes 25 sachets of Nitrogen (MT5009), Phosphorous (MT5010) and Potassium (MT5002), 3 x 100 mL bottles of extraction solution and 5 plastic test tubes. All results are compared to standards on laminated colour charts.

Mi455 PRO

Mini-titrator for the determination of FREE & TOTAL SULPHUR DIOXIDE in wine analysis

Mi455 PRO is a user-friendly microprocessor-based mini-titrator for the determination of free and total sulphur dioxide in the process of wine making. This mini-titrator will give you direct readings with a range of 0 to 400 ppm. The instrument comes with a pre-programmed analysis method for free and total sulphur dioxide measurements on wine sample.

Specifications	Mi455 PRO Sulphur Dioxide
Range	0 to 400 ppm of SO ₂
Resolution	1 ppm
Accuracy	5% of reading
Method	riper titrimetric method
Principle	equivalence point redox titration
Sample volume	50 mL
ORP electrode	MA924B/1 (included)
Pump debit	0.5 mL/min
Stirring speed	1500 rpm
Environment	0 to 50°C; max RH 95%
Power supply	220V/50 Hz; 10VA
Dimensions	350 x 310 x 250 mm
Weight	5,5 kg

Ordering Information

Mi455 PRO is supplied complete with: Calibration standard SO₂, Titrant SO₂, Alkaline reagent for total SO₂, Acid reagent for total SO₂, Acid reagent for free SO₂, Stabilizer, SO₂, MA924B/1 ORP electrode, small stir bar, 2 x 50 mL beakers, 2 x 25 mL beakers, Refilling Electrolyte Solution 3.5M KCl for ORP electrodes 230 mL bottle, test tube set, O-ring, 1 mL syringe, power cable and instruction manual.



Mi 456 PRO Mini-titrator for the determination of TITRATABLE TOTAL ACIDITY for wine analysis

Mi456 PRO is a user-friendly microprocessor-based mini-titrator for the determination of the titratable total acidity in the process of wine making. This minititrator gives you direct readings in g/L of tartaric acid, with a range of 0.0 to 25.0 g/L. The instrument comes with a pre-programmed analysis method for the titratable total acidity measurements on wine sample.

Specifications	Mi456 PRO Titratable Total Acidity
Range	0.0 to 25.0 g/L of tartaric acid
Resolution	0.1 g/L
Accuracy	5% of reading
Method	acid-base titration method
Principle	end-point titration
pH Calibration	1 point in selected end-point: 7.00 pH or 8.20 pH
Sample volume	2 mL
Temperature Compensation	Automatic from 0.0 to 100.0°C
pH Electrode	MA919B/1 (included)
Temperature Probe	MA831R (included)
Pump debit	0.5 mL/min
Stirring speed	1500 rpm
Environment	0 to 50°C; max RH 95%
Power supply	220V/50 Hz; 10VA
Dimensions	350 x 310 x 250 mm
Weight	5,5 kg

Mi456 PRO is supplied complete with:


Calibration standard TA, Titrant TA, Buffer pH 7.0, Buffer pH 8.2, MA919B/1 pH Electrode, MA831R Temperature probe, MA9011 Refilling Electrolyte Solution 3.5M KCl, for pH electrodes 230 mL bottle, small stir bar, 2 x 50 mL beakers, 2000 µL pipette, test tube set, O-ring, 1 mL syringe, power cable and instruction manual.

Accessories


- MA924B/1 ORP Electrode for Mi455
- MA919B/1 pH Electrode for Mi456
- MA831R Temperature probe for Mi456
- MA9011 Refilling Electrolyte Solution 3.5M KCl, for ORP electrodes, 230 mL bottle
- Mi0009 Small stir bars (5 pcs)
- Mi0020 50 mL beaker (4 pcs)
- Mi0021 25 mL beaker (4 pcs)
- Mi0022 2000 µL pipette (1 pc)
- Mi0023 Pipette tips for 2000 µL pipette (4 pcs)



Measuring pH in meat Using MW102 PRO+ pH portable meter with a MA920B/1 pH electrode



The pH changes occurring in a carcass during the first 24 hours after slaughter are important for the quality of the final meat or meat products. Protein denaturation will occur if pH falls to too low a level or if a relatively low pH sets in at a time after slaughter where the carcass temperature is still high. This will result in meat with poor water holding capacity and in extreme cases in meat that is PSE.



Calibrate the pH meter using pH 7 and pH 4 standardization buffers.


1. Cut meat sample into small pieces.



2. Weight approximately 10 grams into a blender cup. Run duplicates on each sample.



3. Add 100 ml of distilled deionized water and blend for 30 seconds on high speed.




4. Transfer sample to a beaker. Read the pH as soon as possible.



5. By pressing the HOLD key you can activate the hold function. The measured value is frozen on the display and the "HOLD" tag lights up. Release "HOLD" by pressing HOLD key again.

6. Blender cups, beakers and stir bars can be rinsed in distilled water between samples. The pH electrode should be rinsed with distilled water between each sample and periodically rinsed with acetone from a squeeze bottle to remove fat buildup.




Spare Electrodes & Probes












pH, ORP, Conductivity, Dissolved Oxygen

Milwaukee has a wide assortment of pH, ORP, Conductivity and other specialty sensors to meet all your specific requirements.

Finding the right electrode for a specific application is a very important task and in order to solve this selection problem it is important to consider the following: electrode body, reference construction and junction.

Below you will find a list of Milwaukee electrodes and probes with corresponding instruments they are supplied with.



OTHER ELECTRODES & PROBES		
	SE220	Double junction pH electrode with 1 meter cable and gel filled electrolyte solution (MW100 / MW101 / MW102)
	SE300	Double junction orp platinum electrode with 1 meter cable and gel filled electrolyte solution (MW500)
	SE510	Conductivity/TDS probe with 1 meter cable (MW301 / MW401)
	SE520	Conductivity/TDS probe with 1 meter cable (MW302 / MW402)
	SE600	Combination probe for pH/EC/TDS with 1 meter cable (MW801 / MW802)
	MA812/2	Conductivity/TDS probe with 2 meter cable (MC310 / MC410)
	MA814DB/1	4-ring Conductivity/TDS/NaCl/Temperature probe with DIN connector and 1 meter cable (MW170)
	MA815D/1	4-ring Conductivity/TDS/NaCl/Temperature probe with DIN connector and 1 meter cable (MW306)
	MA911B/2	Double junction, gel filled pH electrode with BNC connector, 2 m cable
	MA906BR/1	pH/Temp amplified probe with 1 meter cable (MW105/MW106)
	MA921B/2	Double junction, gel filled ORP electrode with platinum sensor, BNC connector, 2 m cable
	MA831R	Stainless steel Temperature probe (MW150 / MW151 / MW160 / MW180)
	MA840	Polarographic D.O. probe with 4 meter cable (MW600)
	MA845	Dissolved Oxygen and Temperature polarographic probe (MW190)
	MA860	Dissolved Oxygen and Temperature galvanic probe (MW605)

Electrode Selection Guide

pH, ORP, Conductivity, Dissolved Oxygen

Milwaukee has a wide assortment of pH, ORP, Conductivity and other specialty sensors to meet all your specific requirements.

Before selecting an electrode, please consult the table below. The recommended electrodes are the ones best suited to each application, however we also ask you to verify the specifications on pages 9-12.

Special electrodes for specific applications can also be manufactured upon request.



Applications	pH	MA905B/3	MA911B/2	SE220	MA913B/3	MA906BR/1	MA916B/1	MA917B/1	MA918B/1	MA919B/1	MA920B/1	MA991B/1	ORP	MA921B/1	SE300	MA923B/3	MA924B/1	MA925B/3	Conductivity	SE510	D.O.	MA840	MA845	MA860
Agriculture / Soil testing																								
Aquarium																								
Brewing																								
Cheese																								
Dairy products																								
Emulsions																								
Environmental, Pollution																								
Fish farming																								
Food and beverage (general use)																								
Galvanizing waste solution																								
Hi purity water																								
Heavy duty applications																								
In-line applications																								
Laboratory (general use)																								
Meat																								
Paints																								
Paper																								
Photographic chemicals																								
Strong acid																								
Swimming pools																								
Water supply																								
Wine processing																								

Calibration, Maintenance & Cleaning Solutions



Calibration, Maintenance & Cleaning Bottle Solutions	
MA9001	pH 1.68 Calibration Buffer Solution, 230 mL
MA9004	pH 4.01 Calibration Buffer Solution, 230 mL
MA9006	pH 6.86 Calibration Buffer Solution, 230 mL
MA9007	pH 7.01 Calibration Buffer Solution, 230 mL
MA9009	pH 9.18 Calibration Buffer Solution, 230 mL
MA9010	pH 10.01 Calibration Buffer Solution, 230 mL
MA9011	Refilling Electrolyte Solution 3.5M KCl for pH/ORP electrodes, 230 mL
MA9012	Refilling Electrolyte Solution 1M KNO ₃ , 230 mL, food applications
MA9015	Storage Solution for pH/ORP electrodes, 230 mL
MA9016	Cleaning Solution for pH/ORP electrodes, 230 mL
MA9020	200-275 mV ORP Solution, 230 mL
MA9060	12880 µS/cm Conductivity Calibration Solution, 230 mL
MA9061	1413 µS/cm Conductivity Calibration Solution, 230 mL
MA9062	1382 ppm TDS Calibration Solution, 230 mL
MA9063	84 µS/cm Conductivity Calibration Solution, 230 mL
MA9064	80000 µS/cm Conductivity Calibration Solution, 230 mL
MA9065	111.8 mS/cm Conductivity Calibration Solution, 230 mL
MA9066	100% NaCl Calibration Solution, 230 mL
MA9069	5000 µS/cm Conductivity Calibration Solution, 230 mL
MA9070	Zero Oxygen Solution, 500 mL + 12 g
MA9071	Electrolyte Solution for D.O. Probes, 230 mL
MA9112	pH 12.45 Calibration Buffer Solution, 230 mL


Get accurate pH readings!

Milwaukee offers a wide range of calibration, maintenance & Cleaning solutions. They are supplied in 230 mL leak-proof bottles and 20 mL single-use sachets.

The use of calibration and cleaning solutions is fundamental for the correct use of electrodes and for obtaining the most accurate and reproducible readings. Often readings are not correct because the sensors have not been properly cleaned and calibrated.



Certificate of analysis

Certificate of analysis is available only for calibration solutions when ordered in boxes of 16 bottles.



Calibration, Maintenance & Cleaning Solutions

Solution starter kits

<p>pH-Start</p> 	<p>Calibration & maintenance & cleaning solutions for pH meters & testers, including:</p> <p>230 mL bottle MA9004 pH 4.01 Calibration Buffer Solution, 230 mL bottle MA9007 pH 7.01 Calibration Buffer Solution, 230 mL bottle MA9015 Storage Solution, 230 mL bottle MA9016 Cleaning Solution</p>
<p>Combo-Start</p> 	<p>Calibration (pH & EC) & maintenance & cleaning solutions for combo meters & testers, including:</p> <p>230 mL bottle MA9007 pH 7.01 Calibration Buffer Solution, 230 mL bottle MA9061 1413 $\mu\text{S}/\text{cm}$ Conductivity Calibration Solution, 230 mL bottle MA9015 Storage Solution, 230 mL bottle MA9016 Cleaning Solution</p>

20 mL single-use sachets

M10004

pH 4.01

Calibration Buffer Solution (20 mL)

± 0.01 pH @ 25°C/77°F

°C	°F	pH	°C	°F	pH
0	32	4.01	50	122	4.06
5	41	4.00	55	131	4.08
10	50	4.00	60	140	4.09
15	59	4.00	65	149	4.1
20	68	4.00	70	158	4.12
25	77	4.01	75	167	4.14
30	86	4.02	80	176	4.16
35	95	4.03	85	185	4.17
40	104	4.04	90	194	4.19
45	113	4.05	95	203	4.20

DO NOT FREEZE. STORE AT ROOM TEMPERATURE. FOR LABORATORY AND INDUSTRIAL USE ONLY.

M10007

pH 7.01

Calibration Buffer Solution (20 mL)

± 0.01 pH @ 25°C/77°F

°C	°F	pH	°C	°F	pH
0	32	7.13	50	122	6.98
5	41	7.10	55	131	6.93
10	50	7.07	60	140	6.93
15	59	7.05	65	149	6.93
20	68	7.03	70	158	6.93
25	77	7.01	75	167	7.00
30	86	7.00	80	176	7.01
35	95	6.99	85	185	7.02
40	104	6.98	90	194	7.03
45	113	6.98	95	203	7.04

DO NOT FREEZE. STORE AT ROOM TEMPERATURE. FOR LABORATORY AND INDUSTRIAL USE ONLY.

M10030

12880 $\mu\text{S}/\text{cm}$

Conductivity Calibration Solution (20 mL)

@ 25°C/77°F

°C	°F	$\mu\text{S}/\text{cm}$	°C	°F	$\mu\text{S}/\text{cm}$
0	32.0	7150	22	71.6	12150
5	41.0	8220	23	73.4	12390
10	50.0	9330	24	75.2	12640
15	59.0	10480	25	77.0	12880
16	60.8	10723	26	78.8	13130
17	62.6	10950	27	80.6	13370
18	64.4	11190	28	82.4	13620
19	66.2	11430	29	84.2	13870
20	68.0	11670	30	86.0	14120
21	69.8	11910	31	87.8	14370

DO NOT FREEZE. STORE AT ROOM TEMPERATURE. FOR LABORATORY AND INDUSTRIAL USE ONLY.

M10016

Cleaning

Cleaning Solution for pH & ORP Electrodes (20 mL)

@ 25°C/77°F

DO NOT FREEZE. STORE AT ROOM TEMPERATURE. FOR LABORATORY AND INDUSTRIAL USE ONLY.

M10000

Rinse

Electrode Rinse Solution (20 mL)

@ 25°C/77°F

DO NOT FREEZE. STORE AT ROOM TEMPERATURE. FOR LABORATORY AND INDUSTRIAL USE ONLY.

Calibration, Maintenance & Cleaning Sachet Solutions	
M1000AB	Combination pack of pH buffer solutions, including 10 sachets of M10007 (pH 7.01), 5 sachets of M10000 (rinse), 5 sachets of M10004 (pH 4.01), 5 sachets of M10010 (pH 10.01); each sachet supplies 20 mL
M10000B	Rinse Solution - Deionized Water (box of 25x20 ml sachet)
M10004B	pH 4.01 Calibration Buffer Solution (box of 25x20 ml sachet)
M10007B	pH 7.01 Calibration Buffer Solution (box of 25x20 ml sachet)
M10010B	pH 10.01 Calibration Buffer Solution (box of 25x20 ml sachet)
M10016B	Cleaning Solution for electrodes (box of 25x20 ml sachet)
M10030B	12880 $\mu\text{S}/\text{cm}$ Calibration Buffer Solution (box of 25x20 ml sachet)
M10031B	1413 $\mu\text{S}/\text{cm}$ Calibration Buffer Solution (box of 25x20 ml sachet)
M10032B	1382 ppm TDS Calibration Solution (box of 25x20 ml sachet)
M10038B	6.44 ppt TDS Calibration Solution (box of 25x20 ml sachet)
M10080B	800 ppm TDS solution (box of 25x20 ml sachet)

Sachet calibration solutions are practical and ready-to-use

Single-use sachets are sealed against light and air and are ideal for on-the-spot calibration.

- Table of reference temperatures
A label presenting a reference table between pH or conductivity values and temperature is printed on all calibration solution sachets and bottles.
- Opaque packaging prevents UV light to contaminate the solution and alter the value.
- Expiration date and production batch number are reported on all Milwaukee calibration solutions.

Simply open, insert the tester or electrode into the sachet and calibrate. Sachets are sold in boxes of 25 pieces.

Safety data sheets

Safety data sheets are available for all solutions and can be downloaded from our website: <https://milwaukeeinstruments.eu/SUPPORT/MSDS/>

WARRANTY POLICY

Milwaukee warrants its instruments to be free of manufacturing defects as follows: bench meters for 3 years, portable and pocket testers for 2 years and electrode/sensors for 6 months (unless otherwise specified).

The warranty period commences from the original date of sale to the user. Warranty is valid only when the product is used under normal conditions and in accordance with the operating limitations and prescribed maintenance procedures.

Milwaukee reserves the right to make improvements in design, construction and appearance of its products without advance notice.

Instrument service

Warranty and non-warranty service are performed by our technicians in Milwaukee headquarters. All items must have a Return Goods Authorization (RGA) number before returning the goods. This number can be obtained by contacting the Milwaukee technical service department at:

tech@milwaukeeinst.com




FURTHER INFORMATION

Latest updates on new products, technical tips, download MSDS

Visit our corporate site:

www.milwaukeeinstruments.eu

for the latest updates on new products, technical tips, download of MSDS.



SPECIFIC APPLICATION LITERATURE

Specific application catalogues and leaflets are also available and can be downloaded from our site. Alternatively for a hard copy request please kindly send us an e-mail at:

info@milwaukeeinst.com





milwaukee

Instruments for Water Analysis

Authorized Distributor

www.milwaukeeinstruments.eu